

PBE-M2-400

Ubiquiti PowerBeam M2 400 - point to point radio körpüləri qurmaq və müştəriləri xeyli məsafədə baza stansiyalarına qoşmaq üçün nəzərdə tutulmuş airMAX seriyalı cihazdır.



Specifications

Model	PBE-M2-400
Brand	Ubiquiti
WiFi	WiFi5
Tezlik	2.4Ghz
Ötürmə məsafəsi	20 km
PoE	PoE

KEY FEATURES

Operating frequency	2 GHz
Bandwidth	150+ Mbit/s
RAM	64MB DDR2, 8 MB Flash
Network interface	(1) 10/100 Ethernet Port
Channel width	5/8/10/20/30/40 MHz
Working range:	405 - 2475 MHz)
Coverage area	20+ Km
Software	AirOS
Gain	18 dBi
Dimensions	420 x 420 x 289 mm (16.54 x 16.54 x 11.38")
Weight	1.795 kg (4.809 lb)
Housing material	UV resistant plastic for outdoor use
Maximum power consumption	6 W
Power	P.O.E. 24 V, 0.5 A. POE adapter included
Nutrition method	Passive POE. Voltage is supplied via Ethernet (pair 4 and 5 are positive, 7 and 8 are negative)
Working temperature	from -40° to +70° C (-40 to 158° F)
Humidity	from 5 to 95% (with condensation)
Vibration tests	ETSI300-019-1.4
Certificate of conformity	FCC Part 15.247, IC RS210, CE