

# PFS3005-4ET-60

Dahua PFS3005-4ET-60 5 Port PoE Switch; PoE - 60W



Model	PFS3005-4ET-60
Brend	Dahua
Port sayı	5 Port
PoE	PoE
PoE gücü	60 W
Port sürəti	100mb/s

## Specification

Hardware Feature	
Ethernet Port	Port 1-4: 4 × RJ-45 10/100M (PoE) Port 5: 1 × RJ-45 10/100M (uplink)
PoE Power Consumption	Port 1 ≤ 60 W (Hi-PoE) port 2-4 ≤ 30 W total ≤ 60 W
Power Consumption	Idling: 0.8 W Full load: 60 W
Standard	IEEE802.3, IEEE802.3u, IEEE802.3x
PoE	
PoE Protocol	IEEE802.3af/ IEEE802.3at/ Hi-PoE
Power Supply Pin	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
Long Distance	250 m long distance PoE transmission
PoE Power Management	Yes
PoE Watchdog	Yes
Performance	
Switching Capacity	1.8 Gbps
Packet Forwarding Rate	744 Kbps
Packet Buffer Memory	1 Mbit

Flow Control	Enable by default
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Application Humidity	5% - 95% (RH)
General	
Power Input	48 V - 57 V DC
Lighting Protection	Common mode: 4 kV Differential mode: 2 kV
ESD Protection	Air discharge: 8 kV Contact discharge: 6 kV
Wall-mount Installation	Yes
Anti-theft Lock Hole	Yes
Weight	0.30 kg (0.64 lb)
Dimension	130 mm × 85 mm × 26 mm (5.12" × 3.35" × 1.02")

Transmission Performance:		
Switch power supply voltage 53V.		
CAT5E/CAT6. Max. DC resistance < 10 Ω/100 m		
Cable(m)	Load Capacity(W)	Bandwidth(Mbps)
IEEE802.3bt 90 W		
100	71.3	100
150	62	10
200	51	10
250	40	10
Hi-PoE 60 W		
100	53	100
150	50	10
200	47	10
250	37	10
IEEE802.3at 30 W		
100	25.5	100
150	25.5	10
200	25.5	10
250	25.5	10
Note: Data from this table was collected by Dahua test lab and is for reference only . The actual transmission distance may vary due to power consumption of connected devices or the cable type and status.		