

PFS3117-16ET-135

Dahua PFS3117-16ET-135 16 Port POE Switch 135W



| | |
|-------------|------------------|
| Model | PFS3117-16ET-135 |
| Brend | Dahua |
| Port sayı | 16 Port |
| Port sürəti | 100mb/s |
| PoE gücü | 120 W |
| PoE | PoE+ |

Specification

| Technical Specification | | |
|-------------------------|--|---|
| Model | DH-PFS3117-16ET-135 | |
| Standards | IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af, IEEE802.3at, Hi-PoE | |
| Interface | 16 x 10/100Mbps RJ45 1 x Gigabit Combo (RJ45/SFP) | |
| Transfer Method | Store-and-Forward | |
| Switching Capacity | 5.2Gbps | |
| Packet Forwarding Rate | 3.87Mpps | |
| Packet Buffer | 2.75Mbit | |
| PoE Ports(RJ45) | Port 1/2 : Hi-PoE/PoE+/PoE; Port 1-16 : PoE+/PoE | |
| Power Pin Assignment | 1 to 2 port: 1/2/4/5 (+), 3/6/7/8 (-) Other PoE port: 4/5 (+), 7/8 (-) | |
| PoE Budget | 135W | |
| Mode | Default mode | All ports can communicate with each other |
| | Isolation mode | PoE port cannot communicate with each other, but can communicate with the uplink Combo port |
| | CCTV mode | 1 to 8 ports support port priority, optimize port cache, switch all ports can communicate with each other |

| | |
|----------------------|--|
| Extender mode | 1 to 8 port rate down to 10Mbps, the farthest transmission distance of up to 250 meters, all ports can communicate with each other |
|----------------------|--|

| | | |
|-------------------------------|--|------------------------------------|
| Indicators | Per Device | Power: Green MAX : Red |
| | Per Port | Link/Act: Green PoE: Yellow |
| Power Supply | AC 100V~240V 50/60HZ | |
| Dimensions (W x D x H) | 340*200*43 mm (13" metal case) | |
| Environment | Operating Temperature: 0°C ~ 45°C | |
| | Storage Temperature: -40°C ~ 70°C | |
| | Operating Humidity: 10%~90% RH No condensation | |
| | Storage humidity: 5%~90% RH No condensation | |