

# PFS3117-16ET-135

Dahua PFS3117-16ET-135 16 Port POE Switch 135W



## Specifications

Model	PFS3117-16ET-135
Brand	Dahua
Port say?	16 Port
Port sür?ti	100mb/s
PoE gücü	120 W
PoE	PoE+

KEY FEATURES

Technical Specification

<b>Model</b>	DH-PFS3117-16ET-135
<b>Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af, IEEE802.3at, Hi-PoE
<b>Interface</b>	16 x 10/100Mbps RJ45 1 x Gigabit Combo (RJ45/SFP)

Transfer Method Store-and-Forward

<b>Switching</b>	5.2Gbps
<b>Capacity</b>	
<b>Packet</b>	3.87Mpps

Forwarding Rate

<b>Packet Buffer</b>	2.75Mbit
----------------------	----------

PoE Ports(RJ45)

Port 1/2 : Hi-PoE/PoE+/PoE;  
Port 1-16 : PoE+/PoE

Power Pin

Assignment 1 to 2 port: 1/2/4/5 (+), 3/6/7/8 (-)  
Other PoE port: 4/5 (+), 7/8 (-)

<b>PoE Budget</b>	135W
-------------------	------

<b>Mode</b>	<b>Default mode</b>	All ports can communicate with each other
	<b>Isolation mode</b>	PoE port cannot communicate with each other, but can communicate with the uplink Combo port
	<b>CCTV mode</b>	1 to 8 ports support port priority, optimize port cache, switch all ports can communicate with each other
	<b>Extender mode</b>	1 to 8 port rate down to 10Mbps, the farthest transmission distance of up to 250 meters, all ports can communicate with each other

<b>Indicators</b>	<b>Per Device</b>	Power: Green MAX : Red
	<b>Per Port</b>	Link/Act: Green PoE: Yellow

<b>Power Supply</b>	AC 100V~240V 50/60HZ
---------------------	----------------------

<b>Dimensions (W × D × H)</b>	340*200*43 mm (13" metal case)
-------------------------------	--------------------------------

<b>Environment</b>	Operating Temperature: 0°C ~ 45°C
	Storage Temperature: -40°C ~ 70°C
	Operating Humidity: 10%~90% RH No condensation
	Storage humidity: 5%~90% RH No condensation