

PFS3125-24ET-190

Dahua PFS3125-24ET-190 24 Port PoE Switch; PoE - 190W



Model	PFS3125-24ET-190
Brend	Dahua
Port sayı	24 Port
PoE	PoE
PoE gücü	200 W
Port sürati	100mb/s

Specification

Technical Specification		
Model	DH-PFS3125-24ET-190	
Standards	IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af, IEEE802.3at, Hi-PoE	
Interface	24 x 10/100Mbps RJ45 1 x Gigabit Combo (RJ45/SFP)	
Transfer Method	Store-and-Forward	
Switching Capacity	6.8Gbps	
Packet Forwarding Rate	5.06Mbps	
Packet Buffer	4Mbit	
PoE Ports(RJ45)	Port 1/2 : Hi-PoE/PoE+/PoE; Port 1-24 : PoE+/PoE	
Power Pin Assignment	1 to 2 port: 1/2/4/5 (+), 3/6/7/8 (-) Other PoE port: 4/5 (+), 7/8 (-)	
PoE Budget	190W	
Mode	Default mode	All ports can communicate with each other
	Isolation mode	PoE port cannot communicate with each other, but can communicate with the uplink Combo port
	CCTV mode	1 to 8 ports support port priority, optimize port cache, switch all ports can communicate with each other
	Extender mode	1 to 8 port rate down to 10Mbps, the farthest transmission distance of up to 250 meters, all ports can communicate with each other

Indicators	Per Device	Power: Green MAX : Red
	Per Port	Link/Act: Green PoE: Yellow
Power Supply	AC 100V~240V 50/60HZ	
Dimensions (W x D x H)	340*200*43 mm (13" metal case)	

Environment**Operating Temperature: 0°C ~ 45°C****Storage Temperature: -40°C ~ 70°C****Operating Humidity: 10%~90% RH No condensation****Storage humidity: 5%~90% RH No condensation**