

# PFS3125-24ET-190

Dahua PFS3125-24ET-190 24 Port PoE Switch; PoE - 190W



## Specifications

Model	PFS3125-24ET-190
Brand	Dahua
Port say?	24 Port
PoE	PoE
PoE gücü	200 W
Port sür?ti	100mb/s

KEY FEATURES

Technical Specification

**Model** DH-PFS3125-24ET-190

**Standards** IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af, IEEE802.3at, Hi-PoE

**Interface**  
24 x 10/100Mbps RJ45  
1 x Gigabit Combo (RJ45/SFP)

Transfer Method Store-and-Forward

**Switching** 6.8Gbps

**Capacity**

**Packet** 5.06Mbps

**Forwarding Rate**

**Packet Buffer** 4Mbit

**PoE Ports(RJ45)**  
Port 1/2 : Hi-PoE/PoE+/PoE;  
Port 1-24 : PoE+/PoE

**Power Pin Assignment**  
1 to 2 port: 1/2/4/5 (+), 3/6/7/8 (-)  
Other PoE port: 4/5 (+), 7/8 (-)

**PoE Budget** 190W

**Mode**

<b>Default mode</b>	All ports can communicate with each other
<b>Isolation mode</b>	PoE port cannot communicate with each other, but can communicate with the uplink Combo port
<b>CCTV mode</b>	1 to 8 ports support port priority, optimize port cache, switch all ports can communicate with each other
<b>Extender mode</b>	1 to 8 port rate down to 10Mbps, the farthest transmission distance of up to 250 meters, all ports can communicate with each other

**Indicators**

<b>Per Device</b>	Power: Green MAX : Red
<b>Per Port</b>	Link/Act: Green PoE: Yellow

**Power Supply** AC 100V~240V 50/60HZ

**Dimensions (W × D × H)** 340\*200\*43 mm (13" metal case)

**Environment**

Operating Temperature: 0°C ~ 45°C

Storage Temperature: -40°C ~ 70°C

Operating Humidity: 10%~90% RH No condensation

Storage humidity: 5%~90% RH No condensation