

PFS3220-16GT-190

Dahua PFS3220-16GT-190 16 Port Full Gigabit PoE L2 Managed Switch; PoE - 190W



| | |
|-------------|------------------|
| Model | PFS3220-16GT-190 |
| Brend | Dahua |
| Port sayı | 16 Port |
| Tip | Managed |
| PoE | PoE |
| PoE gücü | 200 W |
| Port sürati | 1000mb/s |

Specification

| | |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Certification | |
| Layer | Layer 2 |
| Managed | No |
| Switching Capacity | 52 Gbps |
| Packet Forwarding Rate | 29.76 Mpps |
| Packet Buffer Memory | 4 Mbit |
| MAC Table Size | 8K |
| Standards Compliance | IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z |
| Hardware Feature | |
| Standard Power Supply | Yes |
| PoE | Yes |
| Ethernet Port | 16 |
| Optical Port | 2 |
| Ethernet Port Rate | 1 Gbps |
| Optical Port Rate | 1 Gbps |
| Number of Bussiness Card Slots | Port 1-16: 16 × RJ45 10/100/1000 M (PoE) Port 17-18: 2 × RJ45 10/100/1000 M (uplink) Port 19-20: 2 × SFP 1000 M (uplink) |
| Power Supply | 100V AC-240V AC |
| Operating Temperature | -10°C to 55°C (14°F to 131°F) |
| Operating Humidity | 10%-90% |
| Storage Humidity | 5%-95% |
| Power Consumption | Idling: 7W Full load: 190W |
| PoE | |
| PoE Standard | IEEE802.3af, IEEE802.3at, Hi-PoE, IEEE802.3bt |
| PoE Budget | Port 1-2≤90W, Port 3-16≤30W, totals190W |
| PoE Pin Assignment | PoE/Hi-PoE: 1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-) |

| | |
|----------------------|----------------------------------------------------|
| General | |
| ESD | Air discharge: 8kV Contact discharge: 6kV |
| Thunderproof | Common mode: 4kV Differential mode: 2kV |
| Dimensions | 440 mm × 300 mm × 44 mm (17.32" × 11.81" × 1.73") |
| Packaging Dimensions | 527 mm × 412 mm × 110 mm (20.75" × 16.22" × 4.33") |