

# PFS3220-16GT-190

Dahua PFS3220-16GT-190 16 Port Full Gigabit PoE L2 Managed Switch; PoE - 190W



Model	PFS3220-16GT-190
Brend	Dahua
Port sayı	16 Port
Tip	Managed
PoE	PoE
PoE gücü	200 W
Port sürati	1000mb/s

## Specification

Certification	
Layer	Layer 2
Managed	No
Switching Capacity	52 Gbps
Packet Forwarding Rate	29.76 Mpps
Packet Buffer Memory	4 Mbit
MAC Table Size	8K
Standards Compliance	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z
Hardware Feature	
Standard Power Supply	Yes
PoE	Yes
Ethernet Port	16
Optical Port	2
Ethernet Port Rate	1 Gbps
Optical Port Rate	1 Gbps
Number of Bussiness Card Slots	Port 1–16: 16 × RJ45 10/100/1000 M (PoE) Port 17–18: 2 × RJ45 10/100/1000 M (uplink) Port 19–20: 2 × SFP 1000 M (uplink)
Power Supply	100V AC–240V AC
Operating Temperature	–10°C to 55°C (14°F to 131°F)
Operating Humidity	10%–90%
Storage Humidity	5%–95%

<b>Power Consumption</b>	<b>Idling: 7W</b> <b>Full load: 190W</b>
<b>PoE</b>	
<b>PoE Standard</b>	IEEE802.3af, IEEE802.3at, Hi-PoE, IEEE802.3bt
<b>PoE Budget</b>	Port 1-2≤90W, Port 3-16≤30W, totals190W
<b>PoE Pin Assignment</b>	PoE/Hi-PoE: 1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
<b>General</b>	
<b>ESD</b>	<b>Air discharge: 8kV</b> <b>Contact discharge: 6kV</b>
<b>Thunderproof</b>	<b>Common mode: 4kV</b> <b>Differential mode: 2kV</b>
<b>Dimensions</b>	440 mm × 300 mm × 44 mm (17.32" × 11.81" × 1.73")
<b>Packaging Dimensions</b>	527 mm × 412 mm × 110 mm (20.75" × 16.22" × 4.33")