

PFS3228-24GT-240

Dahua PFS3228-24GT-240 24 Port PoE L2 Managed Switch; PoE - 240W



| | |
|-------------|------------------|
| Model | PFS3228-24GT-240 |
| Brend | Dahua |
| Port sayı | 24 Port |
| Tip | Managed |
| PoE | PoE |
| Port sürəti | 1000mb/s |
| PoE gücü | 250 W |

Specification

| | |
|--------------------------------|--|
| Certification | |
| Layer | Layer 2 |
| Managed | No |
| Switching Capacity | 52 Gbps |
| Packet Forwarding Rate | 38.688 Mpps |
| Packet Buffer Memory | 4 Mbit |
| MAC Table Size | 8K |
| Standards Compliance | IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z |
| Hardware Feature | |
| Standard Power Supply | Yes |
| PoE | Yes |
| Ethernet Port | 24 |
| Optical Port | 2 |
| Ethernet Port Rate | 1 Gbps |
| Optical Port Rate | 1 Gbps |
| Number of Bussiness Card Slots | Port 1–24: 24 × RJ45 10/100/1000 M (PoE) Port 25–26: 2 × RJ45 10/100/1000 (uplink) Port 27–28: 2 × SFP 1000 M (uplink) |
| Power Supply | 100V AC–240V AC |
| Operating Temperature | –10°C to 55°C (14°F to 131°F) |
| Operating Humidity | 10%–90% |
| Storage Humidity | 5%–95% |

| | |
|-----------------------------|--|
| Power Consumption | Idling: 8W Full load: 240W |
| PoE | |
| PoE Standard | IEEE802.3af/ IEEE802.3at/ Hi-PoE/IEEE802.3bt |
| PoE Budget | Port 1-2≤90W, Port 3-24≤30W, totals240W |
| PoE Pin Assignment | PoE/Hi-PoE: 1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-) |
| General | |
| ESD | Air discharge: 8kV Contact discharge: 6kV |
| Thunderproof | Common mode: 4kV Differential mode: 2kV |
| Dimensions | 440 mm × 300 mm × 44 mm (17.32" × 11.81" × 1.73") |
| Packaging Dimensions | 527 mm × 412 mm × 110 mm (20.75" × 16.22" × 4.33") |