

# POE200H

CUDY POE200H 30W 2.5GBPS PoE+/PoE INJECTOR, müasir şəbəkə infrastrukturunun artan sürət və güc tələblərini qarşılamaq üçün dizayn edilmiş yüksək performanslı 2.5 Gigabit PoE+ İnjektordur. Standart 1Gbps sürətindən 2.5 dəfə daha sürətli məlumat ötürmə qabiliyyətinə malik olan bu cihaz, xüsusilə yeni nəsil Wi-Fi 6 və Wi-Fi 7 Access Point (paylayıcı) cihazlarının tam potensialını üzə çıxarmaq üçün əvəzolunmazdır.



## Specifications

Model	POE200H
Brand	Cudy
PoE d?st?yi	PoE+
Volt	56V
Watt	30W

KEY FEATURES

<b>Model</b>	<b>POE200H 1.0</b>
<b>802.3 Protocols</b>	<ul style="list-style-type: none"> <li>• 802.3i 10 Mbps over Twisted Pair</li> <li>• 802.3u 100 Mbps over Twisted Pair</li> <li>• 802.3ab 1 Gbps over Twisted Pair</li> <li>• 802.3bz 2.5 Gbps over Twisted Pair</li> <li>• 802.3af PoE</li> <li>• 802.3at PoE</li> </ul>
<b>Uplink Stream</b>	<b>1× 2.5GbE</b>
<b>Downlink Stream</b>	<b>1× 2.5GbE, 802.3at/af</b>
<b>Downlink Pin Assignment</b>	<b>Mode A</b>
<b>Transmission Distance</b>	<ul style="list-style-type: none"> <li>• Cat. 5e or higher cable: 100 meters at Gigabit</li> <li>• Cat. 5e or higher cable: 100 meters at 2.5 Gbps</li> <li>• Note: Total cable length from the uplink switch through the PoE adapter to the downlink device is measured as one segment</li> </ul>
<b>Physical Buttons</b>	<b>Reset Button</b>
<b>LED</b>	<b>Power</b>
<b>Power Interfaces</b>	<b>AC Inlet</b>
<b>Power Methods</b>	<b>AC</b>
<b>Power Input</b>	<b>100-240V~ 50/60Hz 0.8A</b>
<b>Max Power Output</b>	<b>30W, 54V@0.56A</b>
<b>Power Protection</b>	<ul style="list-style-type: none"> <li>• Surge Protection</li> <li>• ESD Protection</li> <li>• Overvoltage Protection</li> <li>• Short-Circuit Protection</li> </ul>
<b>EMC</b>	<b>IEC/EN 61000-4-2, Level 3 ESD: Contact: 6kV; Air: 8kV IEC/EN 61000-4-5, Above Level 4 Surge: Power: DM 4kV, CM 4kV; RJ45: CM 4kV</b>
<b>Grounding Methods</b>	<b>Three-Prong Plug</b>
<b>Environment</b>	<b>Ambient Operating Temperature: -10~40 ℃ (14~104 ℉) Storage Temperature: -40~70 ℃ (-40~158 ℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 10%~95% non-condensing</b>
<b>FCC, CE</b>	
<b>Installation</b>	<ul style="list-style-type: none"> <li>• Desktop</li> <li>• Wall-mount</li> </ul>
<b>Dimension</b>	<b>123×51×35 mm 4.84×2.01×1.38 inches</b>
<b>Casing Material</b>	<b>Plastic</b>
<b>Product Weight</b>	<b>150.0 g (5.29 oz.)</b>

- POE200H
- Power Cord
- Mounting Kit
- Installation Guide

**Retail Package Dimension** 193×135×55 mm  
7.6×5.31×2.17 inches

**Retail Package Weight** EU: 346.0 g (12.2 oz.)

**Units per Carton** 40

**Carton Net Weight** EU: 13.8 kg (30.42 lbs)

**Carton Gross Weight** EU: 14.5 kg (31.97 lbs)

**Carton Dimension** 35.2×33.1×32.6 cm  
13.86×13.03×12.83 inches