NOBRAND

POS-1519 15.1" (Black)

Kod: 00-00001301 · POS Sistemlər



OCOM POS-1519 SINGLE BLACK 15.1", pərakəndə satış və xidmət sektoru üçün dizayn edilmiş, yüksək dözümlülüyə malik tək ekranlı kassa aparatıdır. Cihazın 15.1 düymlük (1024x768 rezolyusiyalı) ekranı əksər kassa və mühasibat proqramlarının standart interfeysi ilə mükəmməl uyğunlaşır; görüntülərdə dartılma və ya boşluq yaranmır. Ön panelin tam düz (True-flat) və kənarsız olması ekranın künclərində toz və çirk yığılmasının qarşısını alır. Qara (Black) rəngli cızılmalara davamlı gövdəsi və ağırlaşdırılmış stendi sayəsində, intensiv istifadə zamanı masanın üzərində tam sabit dayanır. Sifarişdən asılı olaraq J1900, Core i3 və ya i5 prosessor konfiqurasiyaları ilə təchiz edilir ki, bu da hər növ biznesin tələbinə uyğun sürət təmin edir.

Texniki göstəricilər

I5 Prosessor	**Touchscreen** Touchscreen
8GB Ram	**128 GB** Yaddaş

Ətraflı məlumat

Model	POS-1519
Name	15.1-inch screen - all in one touch POS Terminal
Frame	The machine body is made of plastic and the base is aluminum.
Color	the car is completely black
Display	
Home screen	15.1 inch touchscreen monitor
Permission	1024*768
Brightness	250cd/m2
Viewing angle	Horizon: 150; Vertical: 140
Touch screen	GG Multi-Point Projected Capacitive Touch
Additional display	15.1-inch display or 12.1-inch display without touch function (optional)
Client display	2*20 VFD display mounted on the rear cover (optional)
Performance	
Motherboard	Intel Celeron J4125 2.0 GHz processor or Intel Core I3/I5 processor of your choice
System memory	1 x DDR4 SO-DIMM slot, support 2400MHz, 4GB/8GB optional
Accumulator	Msata SSD 64GB or higher, up to 256GB
Audio	On Real Tek ALC662 board.
local area network	10/100 Mbps, Realtek RTL8111F network chip Built-in Mini PCI-E slot, support for built-in WIFI module
operating system	Windows7/8/10, built-in, МЫPOS, Linux
Connectivity options	
External I/O port J4125	Power Button*1,12VDC,Connector*1
	LAN: RJ-45*1
	USB*6
	15-pin VGA D-sub connector *1

RS 232*2	
Line out*1, microphone in*1	
Parameters	
MSR	Additional side MSR
Package	
Weight	Net weight 6.5kg, gross weight 8.0kg for one screen
Bag with foam inside	425*275*405mm for single screen, 440*295*425mm for double screen
Wednesday	
Operating Temperature	From 0 to 40 degrees Celsius
Storage temperature	From -10 to 60 degrees Celsius
Working humidity	10%~80% Non-condensing
Storage humidity	10%~90% Non-condensing
Accessories	
Power adapter	200-240V/50-60Hz(default), AC input power 110-240V/50-60Hz, DC output adapter 12V/5A
Power cable	The power cord plug is compatible with US/EU/UK etc. and is available for customized.

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az