

POS-1560R 15.6" (Black)

POS MAZIC 1560R (B) INTEL J64B/RAM 8GB/SSD 128GB/15.6 FHD



| | |
|-------|-------------------------|
| Model | POS-1560R 15.6" (Black) |
| Brend | Import |
| Növ | POS |

Specification

| | |
|-----------|---|
| Processor | <p>Intel® Core™ i5-7200U (3M Cache, 2.50/3.10 GHz(Turbo), 2 Cores)</p> <p>Intel® Core™ i3-7100U (3M Cache, 2.40 GHz, 2 Cores)</p> <p>Intel® Celeron® Processor J3455 (2M Cache, up to 2.3 GHz, 4 Cores)</p> |
| Chipset | <p>Windows (7200U/7100U)</p> <p>Intel® Kaby Lake</p> <p>Windows (J3455)</p> <p>Intel® Apollo Lake</p> |
| Memory | <p>Windows (7200U/7100U)</p> <p>4GB Standard, DDR4L 2133 MT/s, Socket 1 x SODIMM (Max. 32GB)</p> <p>Windows (J3455)</p> <p>4GB Standard, DDR3L 1600 MT/s, Socket 1 x SODIMM</p> |
| Storage | <p>NVME M.2 128G</p> |
| RAID | <p>Windows (7200U/7100U)</p> <p>RAID 0,1 (SATA Only)</p> |
| OS | <p>Windows 10 IoT Enterprise</p> |

| | |
|--------------------------|---|
| Audio | Realtek ALC662-VD |
| Display | <p>Type</p> <p>15.6" TFT LCD, LED Backlight</p> <p>Resolution</p> <p>1366 x 768</p> <p>Brightness</p> <p>400 cd/m² (typ.)</p> <p>Touch Screen</p> <p>Projective Capacitive Touch, AF</p> |
| Interface | <p>Display</p> <p>1 x Display port (USB-C)</p> <p>LAN</p> <p>1 x Gigabit Ethernet, RJ-45</p> <p>Audio</p> <p>1 x Line-out</p> <p>Power DC-IN</p> <p>USB C</p> <p>Cash Drawer Port</p> <p>1 x RJ-11 (Integrated circuit GPIO)</p> |
| USB | <p>5 (Rear 5, USB 3.0 x 2, USB 2.0 x 2, USB C type x 1)</p> <p>3 (Reserved for MSR, SCR, i-Button/Touch Controller)</p> |
| Serial Port | <p>2 (COM 1 reserved MSR/SCR, TX/RX only)</p> <p>(COM2 reserved CDP, TX/RX only)</p> |
| Power | <p>Power Supply</p> <p>Adaptor 12V, 5A / 24V, 6.35A (I/O BOX Option)</p> |
| Physical & Environmental | <p>Operating Temperature</p> <p>0 °C ~ 60 °C at 10% to 90% Humidity</p> <p>Storage Temperature</p> <p>-20 °C ~ 80 °C at 10% to 90% Humidity</p> <p>Dimensions (W x H x D)</p> <p>400 x 380 x 245 (mm), 15.7 x 14.9 x 9.6 (in)</p> <p>Packing Dimension (W x H x D)</p> <p>500 x 170 x 310 (mm), 19.7 x 6.7 x 12.2 (in)</p> <p>Net Weight</p> <p>6.1 Kg, 13.44 lb</p> <p>Packing Weight</p> <p>7 Kg, 15.43 lb</p> <p>Certification</p> <p>CE, FCC, KC</p> <p>Color</p> <p>Matte Dark Black</p> |

| | |
|----------------------------------|---|
| <p>Options & Peripherals</p> | <p>2nd Display</p> <p>9.7" (1024 x 768), 13.3" (1920 x 1080) LCD Display, Optional Touchscreen</p> <p>Customer Display</p> <p>VFD, 20 Columns x 2 Lines</p> <p>I/O Expansion</p> <p>Support I/O Expansion Box</p> <p>Storage</p> <p>NVME M.2 128G</p> <p>Magnetic Stripe Reader</p> <p>Comply with ISO 7811, Support 1 & 2 & 3 Track</p> <p>Smart Card Reader</p> <p>EMV Level 1, 2</p> <p>Dallas</p> <p>Dallas i-button Reader</p> <p>Fingerprint</p> <p>Yes</p> <p>Wall Mount Kit</p> <p>VESA-Compatible 100 x 100(mm)</p> <p>Camera</p> <p>5M USB Interface (Internal) (Factory Option)</p> <p>Speaker</p> <p>2 x 0.7W (Stereo) (Factory Option)</p> <p>WiFi / Bluetooth</p> <p>Combo Module, M.2 (Factory Option)</p> |
|----------------------------------|---|