

QW2100 QuickScan Lite

DATALOGIC QUICKSCAN LITE QW2100



Model	QW2100 QuickScan Lite
Brend	Datalogic
Növ	Skaner
Skaner qoşulma	USB

Specification

Connection interface	HID (keyboard break connection, KBW)
Manufacturer	Datalogic
Model	QW2170
Series	QuickScan
Guarantee	3 года
Input voltage	5 V
Color	black
Equipment dimensions, sm	17,0 x 6,5 x 7,0
Equipment weight, kg	0.119
Protection from dust and moisture	IP42
Humidity, %	5-95%
Operating temperature, °C	from 0 to 50
Storage temperature, °C	from -40 to 70
Drop resistance	from 1.5 m to concrete
Scanning element	1D Linear
Minimum print contrast, %	25
Reading speed, scan/sec	400
Field of view vertical	+/-65°
Field of view horizontal	+/-45°
Reading indicators	light, sound
Reading Barcodes	1D

Recognizable barcodes	1D / LINEAR BARCODES Automatically recognizes all standard 1D barcodes, including the GS1 DataBar™ family of linear codes. POSTAL SCHEDULES Chinese Post SCHEDULE IN STACK Composite EAN/JAN; Composite GS1 DataBar; GS1 DataBar in stack; Extended GS1 DataBar Stacked, Omnidirectional GS1 DataBar Stacked
Scanner type	Wired