

RB4011iGS+5HacQ2HnD-IN

Mikrotik RB4011iGS+5HacQ2HnD-IN dördnövəli 1.4Ghz CPU, 1GB RAM, SFP+ 10Gbps port, ikili diapazon 2.4GHz / 5GHz 4x4 MIMO 802.11a/b/g/n/ac simsiz güclü 10xGigabit port router



Model	RB4011iGS+5HacQ2HnD-IN
Brend	Mikrotik
WIFI	WiFi5
Tezlik	2.4Ghz/5Ghz
Port sürəti	1000 mb/s
Genişlik	Dual band

Specification

Specifications

Details	
Product code	RB4011iGS+5HacQ2HnD-IN
Architecture	ARM 32bit
CPU	AL21400
CPU core count	4
CPU nominal frequency	auto (533 - 1900) MHz
Switch chip model	RTL8367SB
Dimensions	228 x 120 x 30 mm
RouterOS license	5
Operating System	RouterOS v7
Size of RAM	1 GB
Storage size	512 MB
Storage type	NAND
MTBF	Approximately 200'000 hours at 25C
Tested ambient temperature	-40°C to 45°C
IPsec hardware acceleration	Yes

Wireless capabilities

Details	
Wireless 5 GHz Max data rate	1733 Mbit/s
Wireless 5 GHz number of chains	4
Wireless 5 GHz standards	802.11a/n/ac
Antenna gain dBi for 5 GHz	3
Wireless 5 GHz chip model	QCA9984
Wireless 5 GHz generation	Wi-Fi 5
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	3
Wireless 2.4 GHz chip model	R11e-2HnD
Wireless 2.4 GHz generation	Wi-Fi 4
WiFi speed	AC2000

Ethernet

Details	
10/100/1000 Ethernet ports	10

Fiber

Details	
SFP+ ports	1

Peripherals

Details	
MiniPCI-e slots	1
Serial console port	RJ45

Powering

Details	
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-57 V
Max power consumption	44 W
Max power consumption without attachments	23 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	18-57 V

PoE-out

Details	
PoE-out ports	Ether10
PoE out	Passive PoE up to 57V
Max out per port output (input 18-30 V)	600 mA
Max out per port output (input 30-57 V)	420 mA
Max total out (A)	600 mA

Certification & Approvals

Details	
Certification	CE, FCC, IC, EAC, ROHS

Details	
IP	IP20

Other

Details	
PCB temperature monitor	Yes
Voltage Monitor	Yes

Wireless specifications

5 GHz	Transmit (dBm)	Receive Sensitivity
6MBit/s	33	-96
54MBit/s	29	-81
MCS0	33	-96
MCS7	28	-77
MCS9	26	-72

2.4 GHz	Transmit (dBm)	Receive Sensitivity
1MBit/s	28	-100
11MBit/s	28	-94
6MBit/s	29	-96
54MBit/s	25	-80
MCS0	26	-96
MCS7	24	-79