

# RB750UPR2

Mikrotik HEX Lite RB750UPR2 PoE



## Specifications

Model	RB750UPR2
Brand	Mikrotik
Port sür?ti	100 mb/s

**KEY FEATURES**

**Specifications**

	Details
Product code	RB750UPr2
Architecture	MIPSBE
CPU	QCA9531
CPU core count	1
CPU nominal frequency	650 MHz
Switch chip model	QCA9531
Dimensions	113x89x28mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	64 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-40°C to 70°C

**Powering**

	Details
Number of DC inputs	2 (PoE-IN, DC jack)
DC jack input Voltage	8-30 V
Max power consumption	51 W
Max power consumption without attachments	3 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	8-30 V

**PoE-out**

	Details
PoE-out ports	Ether2-Ether5
PoE out	Passive PoE
Max out per port output (input 18-30 V)	1 A
Max total out (A)	2 A

**Ethernet**

	Details
10/100 Ethernet ports	5

**Peripherals**

---

**Details**

<b>Number of USB ports</b>	<b>1</b>
<b>USB Power Reset</b>	<b>Yes</b>
<b>USB slot type</b>	<b>USB type A</b>
<b>Max USB current (A)</b>	<b>1</b>

**Other**

---

**Details**

<b>Current Monitor</b>	<b>Yes</b>
<b>PCB temperature monitor</b>	<b>Yes</b>
<b>Voltage Monitor</b>	<b>Yes</b>

**Certification & Approvals**

---

**Details**

<b>Certification</b>	<b>CE, EAC, ROHS</b>
<b>IP</b>	<b>20</b>