

# RB750UPR2

Mikrotik HEX Lite RB750UPR2 PoE



Model	RB750UPR2
Brend	Mikrotik
Port sürəti	100 mb/s

## Specification

### Specifications

Details	
Product code	RB750UPr2
Architecture	MIPSBE
CPU	QCA9531
CPU core count	1
CPU nominal frequency	650 MHz
Switch chip model	QCA9531
Dimensions	113x89x28mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	64 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-40°C to 70°C

### Powering

Details	
Number of DC inputs	2 (PoE-IN, DC jack)
DC jack input Voltage	8-30 V
Max power consumption	51 W
Max power consumption without attachments	3 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	8-30 V

## PoE-out

Details	
PoE-out ports	Ether2-Ether5
PoE out	Passive PoE
Max out per port output (input 18-30 V)	1 A
Max total out (A)	2 A

## Ethernet

Details	
10/100 Ethernet ports	5

## Peripherals

Details	
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A
Max USB current (A)	1

## Other

Details	
Current Monitor	Yes
PCB temperature monitor	Yes
Voltage Monitor	Yes

## Certification &amp; Approvals

Details	
Certification	CE, EAC, ROHS
IP	20