MIKROTIK

RB951UI-2HND

Kod: 00-00002819 · Access Pointlər



Mikrotik HAP Lite RB951UI-2HND. 5 Ethernet portu və 5-ci portda PoE çıxışı ilə 2.4GHz AP. 600MHz CPU, 128MB RAM və USB port.

Texniki göstəricilər

WiFi4
WIFI

2.4Ghz
Tezlik

PoE
PoE

Ətraflı məlumat

Specifications

Details	
Product code	RB951Ui-2HnD
Architecture	MIPSBE
CPU	AR9344
CPU core count	1
CPU nominal frequency	600 MHz
Dimensions	113x138x29mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	128 MB
Storage size	128 MB
Storage type	NAND
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-20C +60C

Wireless capabilities

Details	
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	2.5
Wireless 2.4 GHz chip model	AR9344
Wireless 2.4 GHz generation	Wi-Fi 4

Ethernet

Details	
10/100 Ethernet ports	5

Peripherals

Details	
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A
Max USB current (A)	1

Powering

Details	
Number of DC inputs	2 (PoE-IN, DC jack)
DC jack input Voltage	8-30 V
Max power consumption	24 W
Max power consumption without attachments	7 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	8-30 V

PoE-out

Details	
PoE-out ports	Ether5
PoE out	Passive PoE
Max out per port output (input 18-30 V)	500 mA
Max total out (A)	500 mA

Certification & Approvals

Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	IP20

Other

Details	
Beeper	Yes

Wireless specifications

2.4 GHz	Transmit (dBm)	Receive Sensitivity
6MBit/s	30	-96
54MBit/s	25	-80
MCS0	30	-96
MCS7	23	-78

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az