

RBD52G-5HacD2HnD-TC (hAP Ac2)

MIKROTİK hAP ac2 (RBD52G-5HacD2HnD-TC)



Model	RBD52G-5HacD2HnD-TC (hAP ac2)
Brend	Mikrotik
WIFI	WiFi5
Genişlik	Dual band
Tezlik	2.4Ghz/5Ghz

Specification

Details	
Product code	RBD52G-5HacD2HnD-TC
Architecture	ARM 32bit
CPU	IPQ-4018
CPU core count	4
CPU nominal frequency	716 MHz
Switch chip model	IPQ-4018
Dimensions	34 x 119 x 98mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	128 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-40°C to 50°C
IPsec hardware acceleration	Yes
Suggested price	\$79.00
Details	

Details	
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	2.5
Wireless 2.4 GHz chip model	IPQ-4018
Wireless 2.4 GHz generation	Wi-Fi 4
Wireless 5 GHz Max data rate	867 Mbit/s
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac
Antenna gain dBi for 5 GHz	2.5
Wireless 5 GHz chip model	IPQ-4018
Wireless 5 GHz generation	Wi-Fi 5
WiFi speed	AC1200
Details	
10/100/1000 Ethernet ports	5
Details	
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A
Max USB current (A)	1
Details	
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-30 V
Max power consumption	21 W
Max power consumption without attachments	16 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	18-28 V
Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	IP20
Details	
Mode button	Yes