

# RE3000

CUDY RE3000 AX3000 WiFi MESH REPEATER Works with Any Wi-Fi Router, Dual-Band Wi-Fi 6, 1× Gigabit Ethernet Port, 50 Connected Devices, Cudy Mesh Satellite, Multi-Band Simultaneous Backhaul, Ethernet Backhaul



## Specifications

Model	RE3000
Brand	Cudy
WiFi	WiFi6
Geni?lik	Dual band
Mesh	Mesh
Tezlik	2.4Ghz/5Ghz

## KEY FEATURES

<b>RE3000 1.0</b>	
<b>Chipset</b>	MT7981BA+MT7976CN
<b>CPU Details</b>	1.3 GHz Dual-Core, ARM Cortex-A53
<b>Flash/ROM</b>	16 MB (128 Mbit) NOR
<b>DDR/RAM</b>	256 MB (2 Gbit) DDR3
<b>5 GHz Wi-Fi Speed</b>	2402 Mbps
<b>2.4 GHz Wi-Fi Speed</b>	574 Mbps
<b>5 GHz Wi-Fi Streams</b>	3T3R (3×3 MIMO)
<b>2.4 GHz Wi-Fi Streams</b>	2T2R (2×2 MIMO)
<b>Wi-Fi Antennas</b>	2× Fixed, 1 × Internal
<b>2.4 GHz Antenna Gain Max</b>	2.1dBi
<b>5 GHz Antenna Gain Max</b>	3.9dBi
<b>FEM or PA/LNA</b>	<ul style="list-style-type: none"> <li>• 5 GHz: 3× Internal</li> <li>• 2.4 GHz: 2× Internal</li> </ul>
<b>Range Performance</b>	<p>Max: 150 m (492 ft)</p> <p>Indoor WiFi range varies depending on the layout and wall materials. See Wall Performance spec for placement suggestions.</p>
<b>Wall Performance</b>	<p>One wooden walls with thickness &lt; 10 cm (4")</p> <p>One concrete wall with thickness &lt; 20 cm (7")</p>
<b>Gigabit RJ45 Ports</b>	1
<b>LED</b>	<ul style="list-style-type: none"> <li>• Signal Strength</li> <li>• WPS</li> <li>• Power</li> </ul>
<b>Physical Buttons</b>	<ul style="list-style-type: none"> <li>• WPS Button</li> <li>• Reset Button</li> </ul>
<b>Power Input</b>	AC Plug
<b>Power Input Note</b>	EU, US, UK Plug are Available
<b>Power Methods</b>	AC
<b>AC</b>	100V ~ 240V
<b>Environment</b>	<p>Operating Temperature: 0 ° ~ 50 ° (32 ° ~ 122 °)</p> <p>Storage Temperature: -40 ° ~ 70 ° (-40 ° ~ 158 °)</p> <p>Operating Humidity: 10% ~ 90% non-condensing</p> <p>Storage Humidity: 5% ~ 90% non-condensing</p>
<b>Grounding Methods</b>	Three-Prong Plug
<b>FCC, CE</b>	
<b>Install in a Daisy Chain</b>	Recommend to install less than 3 repeaters in a wireless chain.
<b>Installation</b>	Plug-In-Socket
<b>Casing Material</b>	Plastic
<b>Dimension</b>	<p>129.6×80×48.6 mm</p> <p>5.1×3.15×1.91 inches</p>

**Product Weight**

- EU: 279 g (9.84 oz.)
- UK: 282 g (9.95 oz.)
- US: 276 g (9.74 oz.)

- RE3000
- Installation Guide

**Retail Package Weight**

- EU: 417 g (14.71 oz.)
- UK: 405 g (14.29 oz.)
- US: 422 g (14.89 oz.)

**Retail Package Dimension** 161×120×96 mm  
6.34×4.72×3.78 inches

**Units per Carton** 30

**Carton Net Weight**

- EU: 12.5 kg (27.56 lbs)
- UK: 12.1 kg (26.68 lbs)
- US: 12.7 kg (28 lbs)

**Carton Gross Weight**

- EU: 13.3 kg (29.32 lbs)
- UK: 13.1 kg (28.88 lbs)
- US: 13.2 kg (29.1 lbs)

**Carton Dimension** 50.4×37.7×34.1 cm  
19.84×14.84×13.43 inches

RE3000 1.0

**Wi-Fi Standards** Wi-Fi 6

**Max Wi-Fi Modulation** 1024-QAM

**Wi-Fi Efficiency**

- OFDMA
- MU-MIMO
- BSS Color

**Max Capacity** 512

**Recommended Client Upper Limit** 50

**Max Wi-Fi Channel Width** 160 MHz

**Wi-Fi Security** WPA/WPA2/WPA3

**WPS** True

**Operation Modes**

- Access Point
- Range Extender

**Mesh** Cudy Mesh Satellite

**Mesh Backhaul**

- Wireless Backhaul
- Wired Backhaul

**Multi-Band Backhaul** true

**LED Control** ture

**Local Control Method**

- Config Web Page
- App Control

**Remote Control Method** App Control © 2026 Cudy. All rights reserved. | Eurotechnology

**Firmware Upgrade**

- Local Update