

RH10

SUNLUX RH10 WIRED 2D BARKOD SCANNER



Model	RH10
Brend	Sunlux
Növ	Skaner
Printerin tipi	Barkod
Skaner qoşulma	USB

Specification

Performance Parameter	
CPU	32bits ARM
Light Source	White LED (Lighting) Red LED(aiming)
Scan Mode	Manual & Automatic & Continuous
Image Sensor	CMOS
Resolution	640x480 Pixels
Scan Speed	60FPS
Scan Precision	≥3mil(code 128 6 digits)
Depth of Field	60~300mm 13mil code39
Print Contrast	≥15%
Interface	USB-HID, USB-VCP, RS232
Decoding Capability	1D:Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8,EAN 13,ISBN, ISSN, GS1 DataBar RSS14, GS1 DataBar Limited, GS1 DataBar Expanded, MSI, Standard 25, Plessey 2D: PDF417, Micro PDF417, QR Code, Data Matrix,Aztec Code, Hanxin code, Maxicode
Physical Parameter	
Size	L x W x H: 170.9x64.4x86.8(mm)
Weight	175g(scanner); 175g(base)
Case Material	ABS+PC

Electrical Parameter	
Input Voltage	DC5V±5%
Working Current	207mA
Standby Current	118mA
Environmental Parameter	
Temperature (Operating)	-10~50
Humidity	5% to 95% (non-condensing)
Temperature (Storage)	-20~60
IP GRADE	IP42
Resistance To Ambient Light	0-100000 lux