

RH10

SUNLUX RH10 WIRED 2D BARKOD SCANNER



| | |
|----------------|--------|
| Model | RH10 |
| Brend | Sunlux |
| Növ | Skaner |
| Printerin tipi | Barkod |
| Skaner qoşulma | USB |

Specification

| Performance Parameter | |
|-----------------------|--|
| CPU | 32bits ARM |
| Light Source | White LED (Lighting) Red LED(aiming) |
| Scan Mode | Manual & Automatic & Continuous |
| Image Sensor | CMOS |
| Resolution | 640x480 Pixels |
| Scan Speed | 60FPS |
| Scan Precision | ≥3mil(code 128 6 digits) |
| Depth of Field | 60~300mm①13mil code39② |
| Print Contrast | ≥15% |
| Interface | USB-HID, USB-VCP, RS232 |
| Decoding Capability | 1D:Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8,EAN 13,ISBN, ISSN, GS1 DataBar③r RSS14④, GS1 DataBar Limited, GS1 DataBar Expanded, MSI, Standard 25, Plessey 2D: PDF417, Micro PDF417, QR Code, Data Matrix,Aztec Code, Hanxin code, Maxicode |
| Physical Parameter | |
| Size | L × W × H: 170.9×64.4×86.8(mm) |
| Weight | 175g(scanner); 175g(base) |
| Case Material | ABS+PC |
| Electrical Parameter | |
| Input Voltage | DC5V±5% |
| Working Current | 207mA |

| | |
|-----------------------------|----------------------------|
| Standby Current | 118mA |
| Environmental Parameter | |
| Temperature (Operating) | -10~50 |
| Humidity | 5% to 95% (non-condensing) |
| Temperature (Storage) | -20~60 |
| IP GRADE | IP42 |
| Resistance To Ambient Light | 0-100000 lux |