

RH10S

SUNLUX RH10S 2D BARCODE SCANNER



Model	RH10S
Brend	Sunlux
Növ	Skaner
Skaner qoşulma	USB

Specification

Performance Parameter	
CPU	32bits ARM
Light Source	White LED (Lighting) Red LED(aiming)
Scan Mode	Manual & Automatic & Continuous
Image Sensor	CMOS
Resolution	640x480 Pixels
Scan Speed	60FPS
Scan Precision	≥3mil(code 128 6 digits)
Depth of Field	60~300mm 13mil code39
Print Contrast	≥15%
Interface	USB-HID, USB-VCP, RS232
Decoding Capability	1D:Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8,EAN 13,ISBN, ISSN, GS1 DataBar, RSS14, GS1 DataBar Limited, GS1 DataBar Expanded, MSI, Standard 25, Plessey 2D: PDF417, Micro PDF417, QR Code, Data Matrix,Aztec Code, Hanxin code, Maxicode
Physical Parameter	
Size	L x W x H: 170.9x64.4x86.8(mm)
Weight	175g(scanner); 175g(base)
Case Material	ABS+PC
Electrical Parameter	
Input Voltage	DC5V±5%
Working Current	260mA

Standby Current	140mA
Environmental Parameter	
Temperature (Operating)	-10~50
Humidity	5% to 95% (non-condensing)
Temperature (Storage)	-20~60
IP GRADE	IP42
Resistance To Ambient Light	0-100000 lux