

RW10

SUNLUX RW10 WIRELESS 2D BARCOD SCANNER



Model	RW10
Brend	Sunlux
Növ	Skaner
Skaner qoşulma	Wireless

Specification

CPU	32bits ARM
Light Source	White LED (Lighting) Red LED(aiming)
Scan Mode	Manual & Automatic & Continuous
Image Sensor	CMOS
Resolution	640x480 Pixels
Scan Speed	60FPS
Scan Precision	±3mil(code 128 6 digits)
Depth of Field	60~300mm(13mil code39)
Print Contrast	≥15%
Interface	USB-HID, USB-VCP
Decoding Capability	1D:Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN8, EAN13, ISBN,ISSN, GS1DataBar, RSS14, GS1 DataBar Limited, GS1 DataBar Expanded, MSI, Standard 25, Plessey 2D: PDF417, Micro PDF417, QR Code, Data Matrix, Aztec Code, Hanxin code, Maxicode
Size	Scanner: 170.9 x 64.4 x 86.8mm Receiver: 15 x 6 x 19mm
Weight	Scanner: 175g±10g (including cable) Receiver: 1.6g
Case Material	ABS+PC
Input Voltage	DC5V±5%
Working Current	312mA
Standby Current	139mA
Indicator	LED indicator light, buzzer

Interface	USB / USB-VCP
Charging mode	TYPE-C cable charging
Charging time	4.5H
Continuous battery life	27H
Battery capacity	2200mAh
Communication methods	2.4G wireless communication, Bluetooth wireless communication
Communication distance	2.4G mode: 100M (open space) Bluetooth mode: 250M (open space)
Humidity	5% to 95% (non-condensing)
Temperature	Operating Temperature: -10~50 Storage Temperature : -20~60
Resistance To Ambient Light	0-100000 lux