

# RW10

SUNLUX RW10 WIRELESS 2D BARCOD SCANNER



## Specifications

Model	RW10
Brand	Sunlux
Qoʻulma	Wireless

## KEY FEATURES

<b>CPU</b>	<b>32bits ARM</b>
<b>Light Source</b>	<b>White LED (Lighting) Red LED(aiming)</b>
<b>Scan Mode</b>	<b>Manual &amp; Automatic &amp; Continuous</b>
<b>Image Sensor</b>	<b>CMOS</b>
<b>Resolution</b>	<b>640x480 Pixels</b>
<b>Scan Speed</b>	<b>60FPS</b>
<b>Scan Precision</b>	<b>≥3mil(code 128 6 digits)</b>
<b>Depth of Field</b>	<b>60~300mm(13mil code39)</b>
<b>Print Contrast</b>	<b>≥15%</b>
<b>Interface</b>	<b>USB-HID, USB-VCP</b>
<b>Decoding Capability</b>	<b>1D:Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN8, EAN13, ISBN,ISSN, GS1DataBar, RSS14, GS1 DataBar Limited, GS1 DataBar Expanded, MSI, Standard 25, Plessey 2D: PDF417, Micro PDF417, QR Code, Data Matrix, Aztec Code, Hanxin code, Maxicode</b>
<b>Size</b>	<b>Scanner: 170.9 x 64.4 x 86.8mm Receiver: 15 x 6 x 19mm</b>
<b>Weight</b>	<b>Scanner: 175g±10g (including cable) Receiver: 1.6g</b>
<b>Case Material</b>	<b>ABS+PC</b>
<b>Input Voltage</b>	<b>DC5V±5%</b>
<b>Working Current</b>	<b>312mA</b>
<b>Standby Current</b>	<b>139mA</b>
<b>Indicator</b>	<b>LED indicator light, buzzer</b>
<b>Interface</b>	<b>USB / USB-VCP</b>
<b>Charging mode</b>	<b>TYPE-C cable charging</b>
<b>Charging time</b>	<b>4.5H</b>
<b>Continuous battery life</b>	<b>27H</b>
<b>Battery capacity</b>	<b>2200mAh</b>
<b>Communication methods</b>	<b>2.4G wireless communication, Bluetooth wireless communication</b>
<b>Communicationdistance</b>	<b>2.4G mode: 100M (open space) Bluetooth mode: 250M (open space)</b>
<b>Humidity</b>	<b>5% to 95% (non-condensing)</b>
<b>Temperature</b>	<b>Operating Temperature: -10~50 StorageTemperature : -20~60</b>
<b>Resistance To Ambient Light</b>	<b>0-100000 lux</b>