eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

DAHUA

SD8A240WA-HNF

Kod: 00-00002059 · Kamera



SD8A240WA-HNF 4MP 40X NETWORK PTZ KAMERA

Texniki göstəricilər

IP Növ	**4 MP** Meqapixel
PTZ Obyektiv	**200m** İşıqlandırma məsafəsi
IP67 Qoruma	**Outdoor** İş mühiti
İR İşıqlandırma	**Metal** Material

Ətraflı məlumat

Camera				
Image Sensor	1/1.8" CMOS			
Pixel	2MP			
Max. Resolution	1920 (H) × 1080 (V)			
Electronic Shutter Speed	1/1 s–1/30,000 s			
Scanning System	Progressive			
Min. Illumination	Color: 0.001 Lux@F1.4 B/W: 0.0001 Lux@F1.4 0 Lux@F1.4 (illuminator on)			
Illumination Distance	500 m (1640.42 ft)			
Illumination On/Off Control	Auto; Manual			
Illuminator Number	10			
Wiper	Smart wiper			
Lens				
Focal Length	5.6 mm–223 mm			
Max. Aperture	F1.4– F4.8			
Field of View	H: 70.3°–1.8°; V: 35.1°–1°; D: 67.5°–2°			
Optical Zoom	40x			
Focus Control	Auto			
Close Focus Distance	0.1 m–1 m (0.33 ft–3.28 ft)			
Iris Control	Auto; Manual			
DORI Distance	Detect	Observe	Recognize	Identify
	2340 m (7677.17 ft)	930 m (3051.18 ft)	460 m (1509.19 ft)	230 m (754.59 ft)
PTZ				

Pan/Tilt Range	Pan: 0°–360° endless Tilt: -30°–90°, auto flip 180°
Manual Control Speed	Pan: 0.1° –240°/s Tilt: 0.1° –100°/s
Preset Speed	Pan: 240°/s; Tilt: 120°/s
Preset	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Scan	5
Speed Adjustment	Yes
Power-off Memory	Yes
Idle Motion	Preset; Tour; Pattern; Scanning
Protocol	DH-SD; Pelco-P/D (auto recognition)
General Intelligence	
Event Trigger	Motion detection; video tampering; scene changing; network disconnection; IP address conflict; illegal access; storage anomaly
IVS	Object abandoned; object missing
Certification	
Certifications	CE: EN55032; EN55024; EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014
Port	
Analog Output	1 port (BNC, 1.0V[p-p], 75Ω)
RS-485	1
Audio I/O	1/1
Alarm I/O	7/2
Power	

Power Supply	DC 36V/2.23A (±25%); Hi-PoE
Power Consumption	26W, 38W (heater on, IR on)
Environment	
Operating Temperature	–40°C to +70°C (–40°F to +158°F)
Operating Humidity	Less than 95% RH
Protection	IP67
Structure	
Casing	Metal
Dimensions	Φ262 mm × 415.6 mm (Φ10.31" × 16.36")
Net Weight	8.5 kg (18.74 lb)
Gross Weight	14.3 kg (31.53 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az