

# SD8A240WA-HNF

SD8A240WA-HNF 4MP 40X NETWORK PTZ KAMERA



## Specifications

Model	SD8A240WA-HNF
Brand	Dahua
??qland?rma	İR
Material	Metal
Növ	IP
Meqapixel	4 MP
Obyektiv	PTZ
??qland?rma m?saf?si	200m
Qoruma	IP67
?? mühiti	Outdoor

KEY FEATURES

<b>Camera</b>				
<b>Image Sensor</b>	1/1.8" CMOS			
<b>Pixel</b>	2MP			
<b>Max. Resolution</b>	1920 (H) × 1080 (V)			
<b>Electronic Shutter Speed</b>	1/1 s–1/30,000 s			
<b>Scanning System</b>	Progressive			
<b>Min. Illumination</b>	Color: 0.001 Lux@F1.4			
	B/W: 0.0001 Lux@F1.4			
	0 Lux@F1.4 (illuminator on)			
<b>Illumination Distance</b>	500 m (1640.42 ft)			
<b>Illumination On/Off Control</b>	Auto; Manual			
<b>Illuminator Number</b>	10			
<b>Wiper</b>	Smart wiper			
<b>Lens</b>				
<b>Focal Length</b>	5.6 mm–223 mm			
<b>Max. Aperture</b>	F1.4– F4.8			
<b>Field of View</b>	H: 70.3°–1.8°; V: 35.1°–1°; D: 67.5°–2°			
<b>Optical Zoom</b>	40x			
<b>Focus Control</b>	Auto			
<b>Close Focus Distance</b>	0.1 m–1 m (0.33 ft–3.28 ft)			
<b>Iris Control</b>	Auto; Manual			
<b>DORI Distance</b>	<b>Detect</b>	<b>Observe</b>	<b>Recognize</b>	<b>Identify</b>
	2340 m	930 m	460 m	230 m
	(7677.17 ft)	(3051.18 ft)	(1509.19 ft)	(754.59 ft)
<b>PTZ</b>				
<b>Pan/Tilt Range</b>	<b>Pan: 0°–360° endless</b>			
	<b>Tilt: -30°–90°, auto flip 180°</b>			
<b>Manual Control Speed</b>	<b>Pan: 0.1° –240°/s</b>			
	<b>Tilt: 0.1° –100°/s</b>			
<b>Preset Speed</b>	<b>Pan: 240°/s; Tilt: 120°/s</b>			
<b>Preset</b>	300			
<b>Tour</b>	8 (up to 32 presets per tour)			
<b>Pattern</b>	5			
<b>Scan</b>	5			
<b>Speed Adjustment</b>	Yes			
<b>Power-off Memory</b>	Yes			
<b>Idle Motion</b>	Preset; Tour; Pattern; Scanning			

---

<b>Protocol</b>	<b>DH-SD; Pelco-P/D (auto recognition)</b>
<b>General Intelligence</b>	
<b>Event Trigger</b>	<b>Motion detection; video tampering; scene changing; network disconnection; IP address conflict; illegal access; storage anomaly</b>
<b>IVS</b>	<b>Object abandoned; object missing</b>
<b>Certification</b>	
<b>Certifications</b>	<b>CE: EN55032; EN55024; EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014</b>
<b>Port</b>	
<b>Analog Output</b>	<b>1 port (BNC, 1.0V[p-p], 75Ω)</b>
<b>RS-485</b>	<b>1</b>
<b>Audio I/O</b>	<b>1/1</b>
<b>Alarm I/O</b>	<b>7/2</b>
<b>Power</b>	
<b>Power Supply</b>	<b>DC 36V/2.23A (±25%); Hi-PoE</b>
<b>Power Consumption</b>	<b>26W, 38W (heater on, IR on)</b>
<b>Environment</b>	
<b>Operating Temperature</b>	<b>-40°C to +70°C (-40°F to +158°F)</b>
<b>Operating Humidity</b>	<b>Less than 95% RH</b>
<b>Protection</b>	<b>IP67</b>
<b>Structure</b>	
<b>Casing</b>	<b>Metal</b>
<b>Dimensions</b>	<b>Φ262 mm × 415.6 mm (Φ10.31" × 16.36")</b>
<b>Net Weight</b>	<b>8.5 kg (18.74 lb)</b>
<b>Gross Weight</b>	<b>14.3 kg (31.53 lb)</b>