

SENSEFACE 2A

ZKTeco SenseFace 2A Face Recognition Terminal ofis və müəssisələr üçün sürətli və dəqiq üz tanıma ilə təhlükəsiz giriş idarəsini təqdim edir. İstifadəsi sadə, etibarlı və yüksək performanslı nəzarət həllidir.



Specifications

Model	SenseFace 2A
Brand	ZKTeco
Cihaz tipi	Controller
Kart tipi	IC
Qoʻulma	Wifi
Barmaq izi	3000
Kart say?	3000

KEY FEATURES

Parameter	SenseFace 2A
Display	2.4" TFT Color LCD (320×240)
Camera	WDR Binocular Camera 1MP
OS	Linux
CPU / RAM / ROM	Dual Core 1GHz / 512MB RAM / 8GB ROM
Speaker / Microphone	8Ω 1W / Omni-directional, -32 dB, SNR 32 dB, Impedance 2.2kΩ
Supplement Light	Yes
Physical Keypad	17 Keys
Fingerprint Sensor	ZK Optical Sensor
Authentication Methods	Fingerprint / Face / Card / Password (Physical Keypad)
Fingerprint Capacity	3,000 templates (1:N)
Face Capacity	1,500 templates (1:N)
Card Capacity	3,000 templates (1:N)
User Capacity	3,000 users
Transaction Capacity	150,000
Max. Password Length	8 digits
Biometric Speed	Fingerprint <0.5s; Facial <0.35s
Touchless Recognition Distance	30–200 cm (Face)
FAR / FRR	FAR ≤0.01% (Face) / ≤0.0001% (Fingerprint); FRR ≤0.02% (Face) / ≤0.01% (Fingerprint)
Biometric Algorithm	ZKFace V4.0, ZKFingerprint V13.0 (Standard) / V10.0 (Optional)
Card Type	ID Card 125 kHz (Standard), IC Card 13.56 MHz (Optional)
Communication	TCP/IP, Optional Wi-Fi, USB, Electric Lock, Door Sensor, Exit Button
Standard Functions	ADMS, DST, Photo Capture, Event Photo Capture, 14-digit User ID, Access Levels, Groups, Holidays, Record Query,
	Schedule Bell, Tamper Switch Alarm, Automatic Status Switch, Multi Authentication,
	SIP Client, ONVIF, AC/TA Push Protocol, HTTPs / SSH Backend, T9 Input
Optional Functions	IC Card, Wi-Fi, Wireless Doorbell
Power Supply	DC 12V 1.5A
Video Intercom	ZKTeco Protocol (TCP/IP) & SIP Protocol, Supports Indoor Monitors & Mobile App
Operating Temperature / Humidity	-5°C to 45°C / 20–80% RH
Dimensions / Weight	205.2 × 74.19 × 33.3 mm / 0.258 kg
Software Supported	ZKBio CVAccess (AC PUSH), ZKBio Time (TA PUSH), ZKBio Zlink (Cloud)
Installation	Wall-mount (Asian Gang Box / Single Gang Box compatible)
Certifications	ISO14001, ISO9001, CE, FCC, RoHS