

ZKTECO

SenseFace 3A

Kod: 00-00005680 · Access Control



ZKTeco SenseFace 3A Face Recognition Terminal ofis və müəssisələr üçün yüksək sürətli və dəqiq üz tanıma ilə təhlükəsiz giriş idarəsini təmin edir. İstifadəsi rahat və etibarlı nəzarət həllidir.

Texniki göstəricilər



Controller

Cihaz tipi



IC

Kart tipi



Wifi

Qoşulma



6000

Barmaq izi



IP65

Qoruma

Ətraflı məlumat

Parameter	SenseFace 3A
Display	2.8" TFT Color Touch LED (240×320)
Camera	WDR Binocular Camera 1MP
OS	Linux
CPU / RAM / ROM	Dual Core 1GHz / 512MB / 8GB
Speaker / Microphone	8Ω, 1W / 1 Omni-directional mic (-42dB, SNR 58dB, Impedance 2.2kΩ)
Supplement Light	No
Fingerprint Sensor	In-Glass Z-ID
Authentication Methods	Fingerprint / Face / Card / Password (Virtual Keypad)
Fingerprint Template Capacity	6,000 (1:N)
Face Template Capacity	3,000 (1:N)
Card Capacity	6,000 (1:N)
User Capacity	6,000 (1:N)
Transaction Capacity	150,000
Max User Password Length	8 digits
Biometric Verification Speed	Fingerprint <0.5s; Face <0.35s
Facial Recognition Distance	30-200 cm
FAR / FRR	Fingerprint FAR ≤0.0001%, FRR ≤0.01%; Face FAR ≤0.01%, FRR ≤0.02%
Biometric Algorithm	ZKFace V4.0 / ZKFingerprint V13.0 / V10.0
Card Type	ID 125kHz (Std), IC 13.56MHz (Optional)
Communication	TCP/IP, optional Wi-Fi, Wiegand I/O, RS485, USB
Access Control Interface	RS485, 3rd party locks, door sensor, exit button
Video Intercom Support	Private Protocol & SIP

Parameter	SenseFace 3A
Standard Functions	ADMS, DST, Photo/Event Capture, T9 input, Bell Scheduling, Anti-passback, Access Levels, HTTPs/SSH, ONVIF Profiles
Optional Functions	IC Card, Wi-Fi, Wireless Doorbell
Power Supply	DC 12V 3A
Operating Temp / Humidity	-5°C to 45°C / 10-90% RH
Dimensions (L×W×H)	166 × 63 × 25 mm
Net Weight	0.185 kg
Ingress Protection	IP65
Certifications	ISO14001, ISO9001, CE, FCC, RoHS
Installation	Wall-mount (Asian Gang Box / Single Gang Box)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az