

SENSEFACE 4A

ZKTeco SenseFace 4A Face Recognition Terminal ofis və müəssisələr üçün yüksək sürətli və dəqiq üz tanıma ilə təhlükəsiz giriş idarəsini təmin edir. İstifadəsi rahat və etibarlı nəzarət həllidir.



Specifications

Model	SenseFace 4A
Brand	ZKTeco
Cihaz tipi	Controller
Kart tipi	IC
Qoʻulma	Wifi
Üz tan?ma	6000
Qoruma	IP65

KEY FEATURES

Parameter	SenseFace 4A
Display	4.3" TFT Color Touch LED (272×480)
Camera	WDR Binocular Camera 1MP
OS	Linux
CPU / RAM / ROM	Dual Core 1GHz / 512MB / 8GB
Speaker / Microphone	8Ω, 1W / 1 Omni-directional mic (-42dB, SNR 58dB, Impedance 2.2kΩ)
Supplement Light	No
Fingerprint Sensor	In-Glass Z-ID
Authentication Methods	Fingerprint / Face / Card / Password (Virtual Keypad)
Fingerprint Template Capacity	8,000 (1:N)
Face Template Capacity	6,000 (1:N)
Card Capacity	8,000 (1:N)
User Capacity	8,000 (1:N)
Transaction Capacity	200,000
Max User Password Length	8 digits
Biometric Verification Speed	Fingerprint <0.5s; Face <0.35s
Facial Recognition Distance	30–200 cm
FAR / FRR	Fingerprint FAR ≤0.0001%, FRR ≤0.01%; Face FAR ≤0.01%, FRR ≤0.02%
Biometric Algorithm	ZKFace V4.0 / ZKFingerprint V13.0 / V10.0
Card Type	ID 125kHz (Std), IC 13.56MHz (Optional)
Communication	TCP/IP, optional Wi-Fi, Wiegand I/O, RS485, USB
Access Control Interface	RS485, 3rd party locks, door sensor, exit button
Video Intercom Support	Private Protocol & SIP
Standard Functions	ADMS, DST, Photo/Event Capture, T9 input, Bell Scheduling, Anti-passback, Access Levels, HTTPs/SSH, ONVIF Profiles
Optional Functions	IC Card, Wi-Fi, Wireless Doorbell
Power Supply	DC 12V 3A
Operating Temp / Humidity	-5°C to 45°C / 10–90% RH
Dimensions (L×W×H)	175×84.5×21.65 mm
Net Weight	0.264 kg
Ingress Protection	IP65
Certifications	ISO14001, ISO9001, CE, FCC, RoHS
Installation	Wall-mount (Asian Gang Box / Single Gang Box)