

SENSEFACE 7A

ZKTeco SenseFace 7A Face Recognition Terminal yüksək sürətli və etibarlı üz tanıma texnologiyası ilə təhlükəsiz giriş idarəsini təmin edir. Ofis, müəssisə və digər obyektlər üçün ideal nəzarət həllidir.



Specifications

Model	SenseFace 7A
Brand	ZKTeco
Cihaz tipi	Controller
Kart tipi	IC
Qoʻulma	Wifi
Barmaq izi	10000
Üz tan?ma	10000
Kart say?	50000
Qoruma	IP65

KEY FEATURES

Parameter	SenseFace 7A
Display	7" TFT Color Touch LED (600×1024)
Camera	WDR Binocular Camera 1MP
OS	Linux
CPU / RAM / ROM	Dual Core 1GHz / 512MB / 8GB
Speaker / Microphone	8Ω, 1W / 1 Omni-directional mic (-32dB)
Supplement Light	No
Fingerprint Sensor	In-Glass Z-ID (7A / 7A Big Cap)
Authentication Methods	Fingerprint / Face / Card / Password
Fingerprint Capacity	10,000 (Std) / 50,000 (Big Cap)
Face Capacity	10,000 (Std) / 50,000 (Big Cap)
Card Capacity	50,000
User Capacity	50,000
Transaction Capacity	300,000
Max User Password Length	8 digits
Biometric Speed	Fingerprint <0.5s, Face <0.35s
Facial Recognition Distance	30–200 cm
FAR / FRR	Fingerprint FAR ≤0.0001%, FRR ≤0.01%; Face FAR ≤0.01%, FRR ≤0.02%
Biometric Algorithm	ZKFace V4.0 / V3.7, ZKFingerprint V13.0 / V10.0
Card Type	ID 125kHz (Std), IC 13.56MHz (Optional)
Communication	TCP/IP, Optional Wi-Fi, Wiegand I/O, RS485, USB
Access Control Interface	RS485, 3rd party locks, door sensor, exit button
Video Intercom Support	Yes, ZKTeco Private & SIP Protocol
Standard Functions	ADMS, DST, Photo Capture, Event Capture, T9 input, Bell Scheduling, Anti-passback, Access Levels, HTTPs/SSH, ONVIF Profiles
Optional Functions	IC Card, Wi-Fi, Wireless Doorbell
Power Supply	DC 12V 3A (Optional)
Operating Temp / Humidity	-5°C to 45°C / 10–90% RH
Dimensions (L×W×H)	238×115×22.3 mm (7A / Big Cap)
Net Weight	0.622 kg
Ingress Protection	IP65
Certifications	ISO14001, ISO9001, CE, FCC, RoHS
Output Contact	2