

SENSEFP M2

ZKTeco SenseFP M2 barmaq izi terminalı yüksək sürətli identifikasiya və etibarlı giriş nəzarəti təmin edir. Sadə quraşdırma və istifadəsi ilə ofislər və iş yerləri üçün mükəmməl təhlükəsizlik həllidir. Giriş qeydiyyatı və vaxt idarəetməsi funksiyaları mövcuddur.



Specifications

Model	SenseFP M2
Brand	ZKTeco
Cihaz tipi	Controller
Kart tipi	IC
Barmaq izi	3000
Kart say?	3000

KEY FEATURES

Category	SenseFP M2
Display	2.8" TFT Color LCD (320×240)
Camera	N/A
Operating System	Linux
CPU	Dual Core @ 1 GHz
RAM	512 MB
ROM	8 GB
Speaker	8 Ω, 1 W
Supplement Light	N/A
Physical Keypad	16 Keys
Fingerprint Sensor	ZK Optical Sensor
Casing Color	Black and White
Authentication Methods	Fingerprint / Card / Password (Keypad)
Fingerprint Capacity	3,000 (1:N)
Face Capacity	N/A
Card Capacity	3,000 (1:N)
User Capacity	3,000 (1:N)
Transaction Capacity	150,000
Max. User Password Length	8 digits
Biometric Authentication Speed	<1 sec (Fingerprint)
Touchless Recognition Distance	N/A
False Acceptance Rate (FAR)	≤0.0001% (Fingerprint)
False Rejection Rate (FRR)	≤0.1% (Fingerprint)
Biometric Algorithm	ZKFingerprint V13.0 (Standard), V10.0 (Optional)
Card Type	ID Card 125 kHz (Standard), IC Card 13.56 MHz (Optional)
Standard Functions	ADMS, DST, Photo Capture, Event Photo Capture, Up to 14-digit User ID, Record Query, Schedule Bell, Tamper Alarm, Automatic Status Switch, Multiple Auth, HTTPS/SSH Backend Access, T9 Keyboard
Optional Functions	IC Card, Wi-Fi, Backup Battery
Power Supply	DC 12V 3A
Backup Battery (Optional)	2,000 mAh Lithium, Max. 4h operating, 7h standby, 5h charging
Operating Temperature	-5°C to 45°C
Operating Humidity	10–90% RH (Non-condensing)
Dimensions (L×W×H)	154 × 138 × 34 mm
Gross Weight	0.99 kg
Supported Software	Mobile App: ZKBio Zlink, Cloud: ZKBio Zlink, On-Premise: ZKBio Time
Installation	Wall-mount (Asian / Single Gang Box compatible)
Certifications	ISO14001, ISO9001, CE, FCC, RoHS