

TAPO C100

TP -LINK HOME SECURITY WI-FI CAMERA TAPO C100 2MP, 12m, Two-Way Audio with Noise Cancellation, MicroSD Card Slot on Camera (Up to 512 GB), ONVIF



Model	TAPO C100
Brend	Tp-Link
Meqapixel	2 MP
Gecə görmə məsafəsi	10m
Səs	İkitərəfli səs
Micro SD	512Gb
Internet	Wifi

Specification

CAMERA	
Image Sensor	1/3" Progressive Scan CMOS Not Starlight Sensor'
Lens	Focal Length: 3.15mm Aperture: F2.0 Field of View: 117° (Diagonal), 98.8°(Horizontal), 53.5°(Vertical)
Motion Range	/
Night Vision	850 nm IR LED (40 ft / 12 m)
Lighting	/
Interface & Button	1× RESET Button 1× MicroSD Card Slot (Up to 512GB)
Hub Compatibility	/
HUB	
Device Compatibility	/
Connection Capacity	/
Interface & Button	/
VIDEO & AUDIO	
Maximum Resolution	1080P HD (1920 x 1080 px)
Frame Rate	15/20/25/30 fps (Default 15fps)
Digital Zoom	/
Video Compression	H.264
Live View	Yes

CAMERA	
Image Enhancement	3D DNR
Audio Input & Output	Built-in Microphone and Speaker
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	91dB (Level measured at 4-inch/10-cm distance)
STORAGE	
Local Storage	MicroSD Card Slot on Camera (Up to 512 GB) General Information about using MicroSD Cards >
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
DETECTION and NOTIFICATIONS	
Sensor	/
AI Detection	Motion Detection Person Detection BabyCry Detection
Activity Zones	Yes
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services) System Notification with Clips (Tapo Care Services)
NETWORK	
Network Connectivity	Connect via Wi-Fi
Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
Ethernet Port	/
RTSP	Yes
ONVIF	Yes
SECURITY	
Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK
POWER	
Power Source	9V DC Power Adapter
Input Voltage	100-240 V, 50/60 Hz
Output Voltage	9 V, 0.6 A (DC Power)
GENERAL	
Certification	/
Smart Integration	Google Assistant, Amazon Alexa
Weather Resistance	/
Mounting Options	Tabletop Ceiling-Mounted
Operating Temperature	0~40
Storage Temperature	-20~60
Operating Humidity	10%~90% RH, Non-condensing
Storage Humidity	5%~90% RH, Non-condensing
Charging Temperature	/
Dimensions (W x D x H)	2.66 x 2.15 x 3.89 in (67.6 x 54.6 x 98.9 mm)
Package Content	Tapo C100 Camera DC Power Adapter Quick Start Guide Mounting Screws Mounting Template