

TAPO C200

TP-LINK TAPO C200 HOME SECURITY WI-FI CAMERA 2MP, 12m, PT Camera, Two-Way Audio with Noise Cancellation, MicroSD Card Slot on Camera (Up to 512 GB)



Model	TAPO C200
Brend	Tp-Link
Meqapixel	2 MP
Gecə görmə məsafəsi	10m
Səs	İkitərəfli səs
Micro SD	512Gb
Internet	Wifi

Specification

CAMERA	
Image Sensor	1/3" Progressive Scan CMOS Not Starlight Sensor'
Lens	Focal Length: 4.0mm Aperture: 2.0 Field of View: 88.3°(Diagonal), 75.2°(Horizontal), 40.8°(Vertical)
Motion Range	Pan Mechanical Range: 340° (360° Pan Coverage) Tilt Mechanical Range: 70° (110.8° Tilt Coverage)
Night Vision	850 nm IR LED (40 ft / 12 m)
Lighting	/
Interface & Button	1× RESET Button 1× MicroSD Card Slot (Up to 512 GB)
Hub Compatibility	/
HUB	
Device Compatibility	/
Connection Capacity	/
Interface & Button	/
VIDEO & AUDIO	
Maximum Resolution	1080P HD (1920 x 1080 px)
Frame Rate	Supports 15 fps by default, 30 fps maximum
Digital Zoom	Supports 9x zoom
Video Compression	H.264

CAMERA	
Live View	Yes
Image Enhancement	3D DNR
Audio Input & Output	Built-in Microphone and Speaker
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	93dB (Level measured at 4-inch/10-cm distance)
STORAGE	
Local Storage	MicroSD Card Slot on Camera (Up to 512 GB) General Information about using MicroSD Cards >
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
DETECTION and NOTIFICATIONS	
Sensor	/
AI Detection	Motion Detection Person Detection BabyCry Detection
Activity Zones	Yes *Only works with Motion Detection.
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services) System Notification with Clips (Tapo Care Services)
NETWORK	
Network Connectivity	Connect via Wi-Fi
Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
Ethernet Port	/
RTSP	Yes
ONVIF	Yes
SECURITY	
Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK
POWER	
Power Source	9V DC Power Adapter
Input Voltage	Adapter Input: 100-240 V, 50/60 Hz
Output Voltage	Adapter Output: 9 V, 0.6 A
GENERAL	
Certification	/
Smart Integration	/
Weather Resistance	/
Mounting Options	Tabletop Ceiling-Mounted
Operating Temperature	0~40
Storage Temperature	-20~60
Operating Humidity	10%~90% RH, Non-condensing
Storage Humidity	5%~90% RH, Non-condensing
Charging Temperature	/
Package Content	Tapo C200 Camera Power Adapter Quick Start Guide Mounting Screws Mounting Template Camera Base Mounting Anchors