

TAPO C501GW 4G

TP-LINK TAPO C501GW 4G LTE OUTDOOR PT SECURITY WI-FI CAMERA

Model	TAPO C501GW 4G
Brend	Tp-Link
Meqapixel	2 MP
Səs	İkitarəfli səs
Gecə görmə məsafəsi	30m
Micro SD	512Gb
Internet	4G
İş mühiti	Outdoor



Specification

CAMERA	
Image Sensor	1/2.9" CMOS Sensor
Lens	Focal Length: 3.17 mm Aperture: F1.65 Field of View: 122° (Diagonal), 105°(Horizontal), 59°(Vertical)
Motion Range	Pan Mechanical Range: 340° (360° Pan Coverage) Tilt Mechanical Range: 60° (130° Tilt Coverage)
Night Vision	850 nm IR LED (98 ft / 29.9 m), starlight color night vision
Interface & Button	1× DC Port 1× Ethernet Port, PoE 1× RESET Button 1× MicroSD Card Slot (Up to 512GB) 1× Nano-SIM Card Slot
VIDEO & AUDIO	
Maximum Resolution	1920 × 1080 px
Frame Rate	15/20/25/30 fps
Video Compression	H.264
Live View	Yes
Audio Input & Output	Built-in Microphone and Speaker
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	99 dB (Level measured at 4-inch/10-cm distance)
STORAGE	

CAMERA	
Local Storage	MicroSD Card Slot on Camera (Up to 512 GB) General Information about using MicroSD Cards >
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
DETECTION and NOTIFICATIONS	
AI Detection	Motion Detection Person Detection Pet Detection Vehicle Detection Tamper Detection Line-Crossing Detection Meow Detection Bark Detection Glass-Breaking Detection
Activity Zones	Yes
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)
NETWORK	
Network Connectivity	3G/4G LTE/LAN Cable
RTSP	Yes
ONVIF	YES (Only Available in Ethernet Mode)
4G	
Frequency	LTE-FDD: B1/3/5/7/8/20/28, LTE-TDD: B38/40/41
POWER	
Power Source	12V DC Power Adapter PoE: 802.3 af/at
Input Voltage	100-240 V, 50/60 Hz
Output Voltage	DC Power:12V, 1A
GENERAL	
Smart Integration	Google Assistant, Amazon Alexa
Weather Resistance	IP66
System Requirements	Tapo App: iOS 9.0 or higher, Andriod 4.4 or higher
Mounting Options	Ceiling-Mounted Wall-Mounted Pole-Mounted (Pole-Mounting loops required but not included)
Operating Temperature	-30℉~60℉
Storage Temperature	-40℉~60℉
Operating Humidity	10%~90% RH, Non-condensing
Storage Humidity	0~90% RH, Non-condensing
Dimensions (W x D x H)	Camera Dimensions: 5.15× 3.31×4.57 in (130. 8× 84.0 × 116.1 mm) Camera Dimensions with included antennas and bracket 5.5 × 4.03 × 9.22 in (139.8 × 102.3 × 234.2 mm)
Package Content	Tapo C501GW Camera Detachable Antenna DC Power Adapter Mounting Template Mounting Bracket Mounting Anchors Bracket Screws Mounting Screws Waterproof Seal Waterproof Cable Attachments Quick Start Guide
Certifications	CE,NTRA,RCM,VCCI,NCC,BSMI,ROHS