

TAPO C510W

TP-LINK TAPO C510W OUTDOOR PT SECURITY WI-FI CAMERA 4MP, 30m, PT Camera, MicroSD Card Slot on Camera (Up to 512 GB), ONVIF



Model	TAPO C510W
Brend	Tp-Link
Meqapixel	4 MP
Gecə görmə məsafəsi	30m
Səs	İkitarəfli səs
Micro SD	512Gb
Internet	Wifi

Specification

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS Sensor
Lens	Focal Length: 3.9 mm Aperture: F2.0 Field of View: 97.23°(Diagonal), 82.3°(Horizontal)@45.31°(Vertical)
Motion Range	Pan Mechanical Range: 340° (360° Pan Coverage) Tilt Mechanical Range: 60° (130° Tilt Coverage)
Night Vision	850 nm IR LED (98 ft / 29.9 m) Color Night Vision
Lighting	2x Built-in Spotlights
Interface & Button	1x RESET Button 1x MicroSD Card Slot
VIDEO & AUDIO	
Maximum Resolution	2304 x 1296 px
Frame Rate	30 fps
Video Compression	H.264
Live View	Yes
Image Enhancement	3DNR WDR
Audio Input & Output	Built-in Microphone and Speaker
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	90 dB (Level measured at 4-inch/10-cm distance)

CAMERA	
STORAGE	
Local Storage	MicroSD Card Slot on Camera (Up to 512 GB) General Information about using MicroSD Cards >
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
DETECTION and NOTIFICATIONS	
AI Detection	Motion detection Person detection Tamper detection
Activity Zones	Yes
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)
NETWORK	
Network Connectivity	Connect via Wi-Fi
Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
RTSP	Yes
ONVIF	Yes
SECURITY	
Security	On-Device Machine Learning 128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK
POWER	
Power Source	9V DC Power Adapter
Input Voltage	100-240 V, 50/60 Hz
Output Voltage	9V, 0.85A (DC Power)
GENERAL	
Smart Integration	Google Assistant, Amazon Alexa
Weather Resistance	IP65
System Requirements	Tapo App: iOS 9.0 or higher, Android 4.4 or higher
Mounting Options	Ceiling-Mounted Wall-Mounted Pole-Mounted (Pole-Mounting loops required but not included)
Operating Temperature	-30~60
Storage Temperature	-40~60
Operating Humidity	10%~90%RH, Non-condensing
Storage Humidity	0~90%RH, Non-condensing
Dimensions (W x D x H)	4.9 x 4.8 x 3.5 in (123.8 x 123 x 90 mm)
Package Content	Tapo C510W Camera Power Adapter Mounting Anchors Mounting Screws Bracket Screws Mounting Template Mounting Bracket Waterproof Seal Quick Start Guide
Certifications	CE, FCC, RoHS, RCM