TIANDY

TC-C320N

Kod: 00-00005083 · Kamera



Tiandy TC-C320N ColorMaker IP kamera ilə gecə də rəngli görüntü əldə edin. 2 MP (1920 × 1080) qətnamə, 2.8 mm sabit lens, 30 m IR məsafəsi, PoE ilə qidalanma və daxili mikrofon sayəsində ev və ofis üçün həm vizual, həm səsli təhlükəsizlik təmin edir.

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
LED İşıqlandırma	**30 m** İşıqlandırma məsafəsi
Mic Mikrofon	**Sabit** Obyektiv
2.8mm Fokus	**Plastik** Material
Indoor İş mühiti	

Ətraflı məlumat

Item	Specification
Image Sensor	1/3" CMOS
Min. Illumination	Color: 0.002 Lux @ (F1.6, AGC ON); B/W: 0 Lux with IR
Shutter Time	1s ~ 1/100000s
Day & Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	120 dB
S/N Ratio	>52 dB
Angle Adjustment	Pan: 0°~340°; Tilt: 0°~75°; Rotate: 0°~360°
Lens Type	Fixed focal
Focal Length	2.8 mm
Lens Mount	M12
Aperture	F1.6 (Fixed)
Field of View	H: 94.4° / V: 53.2° / D: 108.2°
Type	Distance
Detect	41.48 m
Observe	16.46 m
Recognize	8.3 m
Identify	4.1 m
Item	Specification
IR LEDs	2 pcs
IR Distance	Up to 30 m
Wavelength	850 nm
White LEDs	2 pcs
White Light Distance	Up to 15 m
Video Compression	S+265 / H.265 / H.264B / H.264M / H.264H

Item	Specification
Video Bit Rate	32 Kbps ~ 4 Mbps
Audio Compression	G.711A / G.711U
Audio Sampling Rate	8 kHz
Max Resolution	2MP (1920 × 1080 @ 30fps)
Main Stream	PAL: 25fps; NTSC: 30fps (1080P / 720P / 704 / 640 resolutions)
Sub Stream	PAL: 25fps; NTSC: 30fps
BLC / HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto / Semi-Auto / Manual / Sunshine / Nature / Warm Lamp / Daylight Lamp / Filament / Lock
OSD	1 Region, up to 48 characters (16 Chinese), Lattice sizes 16×16 / 32×32 / 48×48
Privacy Mask	4 areas
Defog	Yes
General Alarm	Motion Detection
Exception Alarm	IP Address Conflict
Protocols	RTSP, HTTP, TCP, UDP, ICMP, DHCP, DNS, NTP, IPv4, Telnet, Unicast
Compatibility	ONVIF (Profile S/T), SDK, CGI, Milestone
Remote Connections	≤2
Client	Easy7 VMS
Web Browsers	IE10+, Firefox 52+, Edge 89+, Safari 11+, Chrome 57+
Network Interface	1 × RJ45 (10/100 Base-T)
Web Client Language	English
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Operating Humidity	≤95% RH
Storage Temperature	-30°C ~ 60°C
Storage Humidity	10%~95% RH (non-condensing)
Power Supply	PoE (IEEE 802.3af), Max 2.5W

Item	Specification
Protection	Surge: 4000V; ESD: 6000V
Dimensions	94 × 94 × 78 mm
Package Size	105 × 105 × 85 mm
Gross Weight	0.17 kg

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az