

TC-C32QV-2FNA

TC-C32QV 2FNA-28 2MP 2.8MM SMART-COLOR NETWORK KAMERA. Tiandy TC-C32QV (2FNA-28), qiymət və performans balansını mükəmməl qoruyan, müasir Color Maker texnologiyalı şəbəkə kamerasıdır. Standart kameralardan fərqli olaraq, bu kamera qaranlıq düşdükdə avtomatik olaraq isti (warm) işıqlarını yandıraraq gecə görüntüsünü rəngli rejimdə təqdim edir. 2.8mm geniş bucaqlı linzası (təxminən 100° baxış bucağı) kiçik otaqları və ya həyətyanı sahələri tam əhatə etmək üçün idealdır. Üzərindəki daxili mikrofon sayəsində yalnız görüntünü deyil, səsi də qeydə alır. Kompakt Turret (Qübbə) dizaynı həm tavan, həm də divar montajı üçün uyğundur.



Specifications

Model	TC-C32QV-2FNA
Brand	Tiandy
Növ	IP
Meqapixel	2 MP
Yıdıcıq	LED
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
Yıdıcıq məsafəsi	20 m
Qoruma	IP67
Material	Plastik
Çalışma mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/2.9"CMOS
Min. Illumination	Color:0.0002Lux@(F1.0,AGC ON)
Shutter Time	1s~1/100000s
Smart IR	Yes
WDR	WDR
S/N	>48dB
Angle Adjustment	0~360°(P); 0~80°(T); 0~360°(R)

Lens

Lens Type	Fixed focal lens
Focal Length	2.8mm
Lens Mount	M12
Aperture Range	F1.0
Aperture Type	Fixed
Field of View	99°(H); 53.4°(V); 116.3°(D)
DORI Distance	Detect:40.0m Observe:15.9m Recognize:8.0m Identify:4.0m

Illuminator

White LEDs	2
Whitelight Distance	Up to 15m

Compression

Standard	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H

Video Bit Rate	32k~4Mbps
----------------	-----------

Audio Compression	G.711A/G.711U
-------------------	---------------

Audio Sampling Rate	8kHz
---------------------	------

Image

Max. Resolution	2MP,1920×1080@30fps
Main Stream	PAL:25fps(1920×1080, 1280×720) NTSC:30fps(1920×1080, 1280×720)
Sub Stream	PAL:25fps(704×576, 704×288, 640×360, 352×288) NTSC:30fps(704×480, 704×240, 640×360, 352×240)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32/48*48; Lattice
Privacy Mask	4 black static areas
Defog	Yes
Feature	
Exceptions Alarm	IP Address Conflict
Linkage Method	Trigger Capture

Video Analytics	Smart Alarm
Network	
Protocols	RTSP; HTTP; TCP; UDP; ICMP; DHCP; DNS; NTP; TLS v1.2; IPv4; SSH; Unicast
System	ONVIF(Profile S/T) ; SDK; CGI; Milestone
Compatibility	
Remote Connections ≤2	
Client	Easy7 VMS
Mobile Client	EasyLive Plus
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
Interface	
Communication Interface	1×RJ-45 (10/100 Base-T)
Built-in Mic	1×Built-in Mic
General	
Web Client Language	12 languages English/Spanish/Italian/Turkish/Russian/Thai/French/Polish/Arabic/Vietnamese/Portuguese/Japanese
Operating Temperature	-30℃~60℃(-22℉~140℉)
Operating Humidity ≤95%RH	
Storage Temperature	-30℃~60℃(-22℉~140℉)
Storage Humidity 10%~95%RH(non-condensing)	
Power Supply	DC12V±25%,Max. 4.5W; PoE:IEEE 802.3af,Max. 6W
Protection	Surge4000V; ESD6000V; IP67
Boundary Dimensions	164(L)73(W)73(H)mm
Package Dimensions	180(L)90(W)95(H)mm
GrossWeight	0.32kg