TIANDY

# TC-C32XN

Kod: 00-00005103 · Kamera




TC-C32XN 2MP 2.8MM COLORMAKER NETWORK KAMERA TIANDY

## Texniki göstəricilər

| | |
|---|---|
| **IP**<br>Növ | **2 MP**<br>Meqapixel |
| **LED**<br>İşıqlandırma | **Sabit**<br>Obyektiv |
| **2.8mm**<br>Fokus | **Mic**<br>Mikrofon |
| **30 m**<br>İşıqlandırma məsafəsi | **Plastik**<br>Material |
| **Indoor**<br>İş mühiti | |

## Ətraflı məlumat

| | |
|---|---|
| Camera | |
| Image Sensor | 1/2.9"CMOS |
| Min. Illumination | Color:0.02Lux@(F2.0,AGC ON),B/W:0Lux with IR |
| Shutter Time | 1s~1/100000s |
| Day&Night | IR-cut filter with auto switch (ICR) |
| WDR | DWDR |
| S/N | >37dB |
| Angle Adjustment | 0~340°(P); 0~75°(T); 0~360°(R) |
| Lens | |
| Lens Type | Fixed focal lens |
| Focal Length | 2.8mm |
| Lens Mount | M12 |
| Aperture Range | F2.0 |
| Field of View | 102.8°(H); 57.6°(V); 117.8°(D) |
| DORI Distance | Detect:40.0m Observe:15.9m Recognize:8.0m Identify:4.0m |
| Illuminator | |
| IR LEDs | 2 |
| IR Distance | 30m |
| Wavelength | 850nm |
| Compression Standard | |
| Video Compression | S+265/H.265/H.264B/H.264M/H.264H |
| Video Bit Rate | 32k~4Mbps |
| Audio Compression | G.711A/G.711U |

| | |
|---|---|
| Audio Sampling Rate | 8kHz |
| Image | |
| Max. Resolution | 1920×1080@30fps |
| Main Stream | PAL:25fps(1920×1080, 1280×720, 704×576, 640×480) NTSC:30fps(1920×1080, 1280×720, 704×480, 640×480) |
| Sub Stream | PAL:25fps(704×576, 704×288, 352×288, 640×360) NTSC:30fps(704×480, 704×240, 352×240, 640×360) |
| BLC | Yes |
| HLC | Yes |
| AGC | Yes |
| 3D DNR | Yes |
| White Balance | Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance |
| OSD | Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32/48*48 |
| Privacy Mask | 4 black static areas |
| Defog | Yes |
| Feature | |
| Alarm Trigger | Motion Detection; IP Address Conflict |
| Linkage Method | trigger capture |
| Network | |
| Protocols | HTTP; TCP/IP; UDP; ICMP; DHCP; DNS; NTP; IPv4; Telnet; Unicast |
| System Compatibility | ONVIF Profile S/T; CGI; Milestone |
| Remote Connection | ≤2 |
| Client | Easy7 Smart Client |
| Moblie Client | EasyLive Plus |
| Interface | |

| | |
|---|---|
| Communication Interface | 1*RJ-45,10/100 Mbps self-adaptive Ethernet port |
| General | |
| Web Client Language | 12 languages<br>English/Spanish/Italian/Turkish/Russian/Thai/French/Polish/Arabic/Vietnamese/Portuguese/Japanese |
| Operating Temperature | -30℃~60℃ |
| Operating Humidity | Humidity 95% or less (no condensation) |
| Storage Temperature | -30℃~60℃ |
| Storage Humidity | Humidity 95% or less (no condensation) |
| Power Supply | POE 802.3af,MAX 6W |
| Protection | Surge4000V; ESD6000V |
| Boundary Dimensions | 117(L)117(W)96(H)mm |
| Package Dimensions | 140(L)140(W)120(H)mm |
| GrossWeight | 0.34kg |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az