TIANDY

# TC-C34UN

Kod: 00-00005526 · Kamera




Tiandy 4MP IP kamera motorize 2.8–12mm lens, 80m IR işıqlandırma və 120dB WDR ilə gündüz-gecə aydın görüntü təmin edir. IP67 qorunması, PoE qidalanması, microSD (512GB) dəstəyi, daxilində mikrofon və Tripwire/Perimeter analitikası ilə təhlükəsizliyə tam nəzarət yaradır.

## Texniki göstəricilər

| | |
|---|---|
| **IP**<br>Növ | **4 MP**<br>Meqapixel |
| **Motorized**<br>Obyektiv | **2.8 - 12mm**<br>Fokus |
| **İR**<br>İşıqlandırma | **80 m**<br>İşıqlandırma məsafəsi |
| **Mic**<br>Mikrofon | **IP67**<br>Qoruma |
| **Plastik**<br>Material | **MicroSD**<br>Yaddaş |

**Outdoor**
İş mühiti

## Ətraflı məlumat

| | |
|---|---|
| Camera | |
| Image Sensor | 1/2.9"CMOS |
| Min. Illumination | Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR |
| Shutter Time | 1s~1/100000s |
| Day&Night | IR-cut filter with auto Switch (ICR) |
| Smart IR | Yes |
| WDR | 120dB |
| S/N | >40dB |
| Angle Adjustment | 0~360°(P); 0~90°(T); 0~360°(R) |
| Lens | |
| Lens Type | Motorized |
| Focal Length | 2.8~12mm |
| Lens Mount | Φ14 |
| Aperture Range | F1.6 |
| Aperture Type | Fixed |
| Field of View | 104.7°~30.3°(H); 56.5°~17.2°(V); 120.9°~34.8°(D) |
| DORI Distance | W: Detect:56.0m Observe:22.2m Recognize:11.2m Identify:5.6m<br>T: Detect:240.0m Observe:95.2m Recognize:48.0m Identify:24.0m |
| Illuminator | |
| IR LEDs | 4 |
| IR Distance | Up to 80m |
| Wavelength | 850nm |
| Compression Standard | |

| | |
|---|---|
| Video Compression | S+265/H.265/H.264B/H.264M/H.264H |
| Video Bit Rate | 32k~6Mbps |
| Audio Compression | G.711A/G.711U |
| Audio Sampling Rate | 8kHz |
| Image | |
| Max. Resolution | 4MP,2688×1520@25fps |
| Main Stream | PAL:25fps(2688×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720) NTSC:24(2688×1520, 2560×1440), 30fps(2304×1296, 1920×1080, 1280×720) |
| Sub Stream | PAL:25fps(704×576, 704×288, 640×360, 352×288) NTSC:30fps(704×480, 704×240, 640×360, 352×240) |
| BLC | Yes |
| HLC | Yes |
| AGC | Yes |
| 3D DNR | Yes |
| White Balance | Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance |
| ROI | 8 rectangular static areas |
| OSD | Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32/48*48/64*64 |
| Privacy Mask | 4 black static areas |
| Defog | Yes |
| Feature | |
| General Alarm | Motion Detection; Mask Alarm |
| Exceptions Alarm | Disk Full; Disk R/W Error; IP Address Conflict |
| Linkage Method | Trigger Recording; Trigger Capture; Notify Surveillance Center |
| Video Analytics | Tripwire; Perimeter |

| | |
|---|---|
| Rules of Behavior Analyse In 1 Scene | 2 |
| Network | |
| ANR | Yes |
| Protocols | HTTP; HTTPS; TCP/IP; UDP; UPnP; ICMP; DHCP; DNS; DDNS; Easy DDNS; NTP; TLS v1.2; QoS; IPv4; SSH; Unicast; FTP |
| System Compatibility | P2P(Mutually exclusive with Profile G); ONVIF(Profile S/T/G) ; SDK; CGI; Milestone; RTSP |
| Remote Connection | ≤2 |
| Client | Easy7 VMS |
| Moblie Client | EasyLive Plus |
| Web | IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+ |
| Interface | |
| Communication Interface | 1*RJ-45 (10/100 Base-T) |
| Built-in Mic | Yes |
| Reset Button | Yes |
| On-board Storage | Support microSD/microSDHC/microSDXC card,up to 512GB |
| RTC | Yes |
| General | |
| Web Client Language | 19 languages Simple Chinese/Traditional Chinese/English/Spanish/Korean/Italian<br>Turkish/Russian/Thai/French/Polish/Dutch/Hebrew/Arabic/Vietnamese/German/Ukrainian/Portuguese/Albanian |
| Operating Temperature | -30℃~60℃(-22℉~140℉) |
| Operating Humidity | ≤95%RH |

| | |
|---|---|
| Storage Temperature | -30℃~60℃(-22℉~140℉) |
| Storage Humidity | 10%~95%RH(non-condensing) |
| Power Supply | DC12V±25%,Max. 6.5W; PoE:IEEE 802.3af,Max. 7W |
| Protection | Surge4000V; ESD6000V; IP67 |
| Boundary Dimensions | 204(L)84(W)76(H)mm |
| Package Dimensions | 215(L)95(W)120(H)mm |
| GrossWeight | 0.57kg |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az