

TC-C36QN-2ENA

TC-C36QN 2ENA-28 6MP 2.8MM COLOR MAKERNETWORK KAMERA. Tiandy TC-C36QN (2ENA-28), yüksək təhlükəsizlik tələb edən obyektlər üçün nəzərdə tutulmuş 6MP (3072x2048) çözünürlüklü şəbəkə kamerasıdır. Bu yüksək qətnamə, görüntünü yaxınlaşdırdıqda (zoom) detalların (üz cizgiləri, nömrə nişanları) itməməsini təmin edir. Color Maker seriyasına aid olduğu üçün, qaranlıqda avtomatik yanan isti (warm) LED işıqları sayəsində gecə görüntüsünü tam rəngli təqdim edir. 2.8mm linzası geniş ərazini nəzarətdə saxlamağa imkan verir. Metal və plastik qarışığı olan möhkəm korpusu IP67 standartına cavab verir, yəni yağışa və toza qarşı tam davamlıdır.



Specifications

Model	TC-C36QN-2ENA
Brand	Tiandy
Növ	IP
Meqapixel	5 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	30 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Plastik
Çalışma mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/2.7"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	WDR
S/N	>52dB
Angle Adjustment	0~360°(P); 0~80°(T); 0~360°(R)

Lens

Lens Type	Fixed focal lens
Focal Length	2.8mm
Lens Mount	M12
Aperture Range	F1.6
Aperture Type	Fixed
Field of View	112.1°(H); 60.4°(V); 128.7°(D)
DORI Distance	Detect:56m Observe:22.2m Recognize:11.2m Identify:5.6m

Illuminator

IR LEDs	2
IR Distance	Up to 30m
Wavelength	850nm
White LEDs	2
Whitelight Distance	Up to 15m

Compression

Standard	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k~6Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz

Image

Max. Resolution	6MP,3200×1800@30fps
Main Stream	PAL:25fps(3200×1800,2880×1620,2560×1440, 2304×1296, 1920×1080, 1280×720) NTSC:30fps(3200×1800,2880×1620,2560×1440, 2304×1296, 1920×1080, 1280×720)
Sub Stream	PAL:25fps(704×576, 704×288, 640×360, 352×288) NTSC:30fps(704×480, 704×240, 640×360, 352×240)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters; 16*16/32*32/48*48/64*64/96*96; Lattice
Privacy Mask	4 black static areas

Defog	Yes
Feature	
General Alarm	Smart Alarm(human and vehicle detection)
Exceptions Alarm	IP Address Conflict
Linkage Method	Trigger Capture
Network	
Protocols	RTSP; HTTP; TCP; UDP; ICMP; DHCP; DNS; NTP; IPv4; SSH; Unicast
System Compatibility	P2P(Mutually exclusive with Onvif); ONVIF(Profile S/T) ; SDK; CGI; Milestone
Remote Connection	≤2
Client	Easy7 VMS
Moblie Client	EasyLive Plus
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
Interface	
Communication Interface	1×RJ-45 (10/100 Base-T)
Built-in Mic	1×Built-in Mic
General	
Web Client Language	12 languages English/Spanish/Italian/Turkish/Russian/Thai/French/Polish/Arabic/Vietnamese/Portuguese/Japanese
Operating Temperature	-30℃~60℃(-22℉~140℉)
Operating Humidity	≤95%RH
Storage Temperature	-30℃~60℃(-22℉~140℉)
Storage Humidity	10%~95%RH(non-condensing)
Power Supply	PoE:IEEE 802.3af,Max. 5W
Protection	Surge4000V; ESD6000V; IP67
Boundary Dimensions	164(L)73(W)73(H)mm
Package Dimensions	180(L)90(W)95(H)mm
GrossWeight	0.3kg