

TC-H334S

TC-H334S PT WIFI NETWORK KAMERA TIANDY



Specifications

Model	TC-H334S
Brand	Tiandy
Meqapixel	3 MP
Gec? görm? m?saf?si	50m
S?s	İkiterəfli səs
Micro SD	512Gb
Qo?ulma	Wifi
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/2.8"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	DWDR
S/N	>38dB
Angle Adjustment	0~340°(P); 15~110°

Lens

Lens Type	Fixed focal lens
Focal Length	4mm
Lens Mount	M12
Aperture Range	F1.6
Aperture Type	Fixed
Field of View	87.7°(H); 46.7°(V); 98.6°(D)
DORI Distance	Detect:65.3m Observe:25.9m Recognize:13.1m Identify:6.5m

Illuminator

IR LEDs	2
IR Distance	Up to 50m
Wavelength	850nm
White LEDs	2
Whitelight Distance	15m

Compression Standard

Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k~4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz/16kHz

Image

Max. Resolution	3MP,2304×1296@25fps
Main Stream	PAL:25fps(2304×1296, 1920×1080, 1280×720, 704×576, 640×480) NTSC:24fps(2304×1296), 30fps(1920×1080, 1280×720, 704×480, 640×480)
Sub Stream	PAL:25fps(704×576, 704×288, 640×360, 352×288) NTSC:30fps(704×480, 704×240, 640×360, 352×240)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32
Privacy Mask	4 black static areas
Defog	Yes

Feature

Exceptions Alarm	Voltage Alarm; Disk Full; Disk R/W Error; IP Address Conflict
Linkage Method	Trigger Sound; Trigger Warmlight; Trigger Recording; Trigger Capture; Notify Surveillance Center; Alarm Output
Auto-Tracking	Yes
Network	
ANR	Yes
Protocols	HTTP; TCP/IP; UDP; ICMP; DHCP; DNS; NTP; TLS v1.2; IPv4; Telnet; Unicast; FTP
System Compatibility	ONVIF(Profile S/T/G) ; SDK; CGI; Milestone; RTSP
Remote Connection	≤2
Client	Easy7 VMS
Moblie Client	EasyLive Plus
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+

Wi-Fi

Transmission DistanceUp tp 30m(based on actual environment)

Wireless Standard	IEEE802.11b/ 802.11g/802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20/40MHz
Wi-Fi Security	WPA-PSK/WPA2-PSK

Interface

Communication 1*RJ-45 (10/100 Base-T)

Interface

Built-in Mic	Yes
Built-in Speaker	Yes
Reset Button	Yes
On-board Storage	Support microSD/microSDHC/microSDXC card,up to 512GB

General

Web Client Language 2 languages English/Turkish

Operating Temperature -30~60(-22~140)

Temperature

Operating Humidity	≤95%RH
Storage Temperature	-30~60(-22~140)
Storage Humidity	10%~95%RH(non-condensing)
Power Supply	DC12V±25%,Max. 12W

Protection Surge4000V; ESD6000V; IP66

Boundary Dimensions 264(L)165(W)140(H)mm

Package Dimensions 185(L)155(W)285(H)mm

GrossWeight 1.22kg