

## TC-H363N

TC-H363N 2\*3MP PT WIFI NETWORK KAMERA TIANDY, 2\*3MP dual lens texnologiyası ilə geniş bucaq və yüksək dəqiqlikdə görüntü təqdim edir. PT (Pan/Tilt) idarəetməsi və WiFi bağlantısı ilə rahat quraşdırma imkanı yaradır. Açıq və qapalı məkanlar üçün ideal IP kamera həllidir.



### Specifications

Model	TC-H363N
Brand	Tiandy
Meqapixel	3 MP
Qo?ulma	Wifi
S?s	Mikrofon
Gec? görm? m?saf?si	50m
Micro SD	512Gb
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/3"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto Switch (ICR)
Smart IR	Yes
WDR	DWDR
S/N	>40dB
Angle Adjustment	Panorama:-60~60°(P) Details:0~345°(P); Panorama:5~15° Details:-15~90°

Lens

Lens Type	Fixed focal lens
Focal Length	4mm
Lens Mount	M12
Aperture Range	F1.6
Aperture Type	Fixed
Field of View	Panorama:81.3°(H); Detail:81.3°(H); Panorama:44.4°(V); Detail:44.4°(V); Panorama:94.4°(D); Detail:94.4°(D)
DORI Distance	Detect:59.26m Observe:23.52m Recognize:11.85m Identify:5.93m

Pan&Tilt

Pan Speed	30°/s
Tilt Speed	25°/s
Preset	255

Illuminator

IR LEDs	Panorama:4 Detail:4
IR Distance	Up to 50m
Wavelength	850nm
White LEDs	Panorama:4 Detail:4
Whitelight Distance	15m
Red and Blue Alarm	Yes

Flash

Compression Standard

Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k~4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz/16kHz

Image

Max. Resolution	Panorama:3MP,2304×1296@15fps Detail:3MP,2304×1296@15fps
-----------------	---

Main Stream

Panorama: PAL:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480) NTSC:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480)

Detail: PAL:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480) NTSC:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480)

<b>Sub Stream</b>	Panorama: PAL:15fps(704×576, 704×288, 640×360, 352×288) NTSC:15fps(704×480, 704×240, 640×360, 352×240) Detail: PAL:15fps(704×576, 704×288, 640×360, 352×288) NTSC:15fps(704×480, 704×240, 640×360, 352×240)
<b>BLC</b>	Yes
<b>HLC</b>	Yes
<b>AGC</b>	Yes
<b>3D DNR</b>	Yes
<b>White Balance</b>	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
<b>OSD</b>	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32/48*48
<b>Privacy Mask</b>	4 black static areas
<b>Defog</b>	Yes
<b>Feature</b>	
<b>Exceptions Alarm</b>	Voltage Alarm; Disk Full; Disk R/W Error; IP Address Conflict
<b>Linkage Method</b>	Trigger Sound; Trigger Recording; Trigger Capture; Notify Surveillance Center
<b>Video Analytics</b>	Smart Alarm
<b>Auto-Tracking</b>	Yes
<b>Network</b>	
<b>ANR</b>	Yes
<b>Protocols</b>	HTTP; TCP/IP; UDP; ICMP; DHCP; DNS; NTP; TLS v1.2; IPv4; SSH; Unicast; FTP
<b>System Compatibility</b>	SDK; CGI
<b>Remote Connection</b>	≤2
<b>Client</b>	Easy7 VMS
<b>Moblie Client</b>	EasyLive Plus
<b>Web</b>	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
<b>Wi-Fi</b>	
<b>Transmission</b>	Up tp 50m( based on actual environment)
<b>Distance</b>	
<b>Wireless Standard</b>	IEEE802.11b/ 802.11g/802.11n
<b>Frequency Range</b>	2.4 GHz ~ 2.4835 GHz
<b>Channel Bandwidth</b>	20/40MHz
<b>Wi-Fi Security</b>	WPA-PSK/WPA2-PSK
<b>Interface</b>	
<b>Communication</b>	1*RJ-45 (10/100 Base-T)
<b>Interface</b>	
<b>Built-in Mic</b>	Yes
<b>Built-in Speaker</b>	Yes
<b>Reset Button</b>	Yes
<b>On-board Storage</b>	Support microSD/microSDHC/microSDXC card,up to 512GB
<b>General</b>	
<b>Web Client Language</b>	3 languages Simple Chinese/English/Vietnamese
<b>Operating</b>	-30~60(-22~140)
<b>Temperature</b>	
<b>Operating Humidity</b>	≤95%RH
<b>Storage Temperature</b>	-30~60(-22~140)
<b>Storage Humidity</b>	10%~95%RH(non-condensing)
<b>Power Supply</b>	DC12V±25%,Max. 13W © 2026 Tiandy. All rights reserved.   Eurotechnology
<b>Protection</b>	Surge4000V; ESD6000V; IP66