TIANDY

TC-H363N

Kod: 00-00005438 · Wifi kamera



TC-H363N 2*3MP PT WIFI NETWORK KAMERA TIANDY, 2×3MP dual lens texnologiyası ilə geniş bucaq və yüksək dəqiqlikdə görüntü təqdim edir. PT (Pan/Tilt) idarəetməsi və WiFi bağlantısı ilə rahat quraşdırma imkanı yaradır. Açıq və qapalı məkanlar üçün ideal IP kamera həllidir.

Texniki göstəricilər

3 MP Meqapixel	**Wifi** Qoşulma
Mikrofon Səs	**50m** Gecə görmə məsafəsi
512Gb Micro SD	**Outdoor** İş mühiti

Ətraflı məlumat

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto Switch (ICR)
Smart IR	Yes
WDR	DWDR
S/N	>40dB
Angle Adjustment	Panorama:-60~60°(P) Details:0~345°(P); Panorama:5~15° Details:-15~90°
Lens	
Lens Type	Fixed focal lens
Focal Length	4mm
Lens Mount	M12
Aperture Range	F1.6
Aperture Type	Fixed
Field of View	Panorama:81.3°(H); Detail:81.3°(H); Panorama:44.4°(V); Detail:44.4°(V); Panorama:94.4°(D); Detail:94.4°(D)
DORI Distance	Detect:59.26m Observe:23.52m Recognize:11.85m Identify:5.93m
Pan&Tilt	
Pan Speed	30°/s
Tilt Speed	25°/s
Preset	255
Illuminator	
IR LEDs	Panorama:4 Detail:4
IR Distance	Up to 50m
Wavelength	850nm

White LEDs	Panorama:4 Detail:4
Whitelight Distance	15m
Red and Blue Alarm Flash	Yes
Compression Standard	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k~4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz/16kHz
Image	
Max. Resolution	Panorama:3MP,2304×1296@15fps Detail:3MP,2304×1296@15fps
Main Stream	Panorama: PAL:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480) NTSC:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480) Detail: PAL:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480) NTSC:15fps(2304×1296, 1920×1080, 1280×720, 704x576, 640x480)
Sub Stream	Panorama: PAL:15fps(704×576, 704×288, 640×360, 352×288) NTSC:15fps(704×480, 704×240, 640×360, 352×240) Detail: PAL:15fps(704×576, 704×288, 640×360, 352×288) NTSC:15fps(704×480, 704×240, 640×360, 352×240)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; 16*16/32*32/48*48
Privacy Mask	4 black static areas

Defog	Yes
Feature	
Exceptions Alarm	Voltage Alarm; Disk Full; Disk R/W Error; IP Address Conflict
Linkage Method	Trigger Sound; Trigger Recording; Trigger Capture; Notify Surveillance Center
Video Analytics	Smart Alarm
Auto-Tracking	Yes
Network	
ANR	Yes
Protocols	HTTP; TCP/IP; UDP; ICMP; DHCP; DNS; NTP; TLS v1.2; IPv4; SSH; Unicast; FTP
System Compatibility	SDK; CGI
Remote Connection	≤2
Client	Easy7 VMS
Moblie Client	EasyLive Plus
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
Wi-Fi	
Transmission Distance	Up tp 50m(based on actual environment)
Wireless Standard	IEEE802.11b/ 802.11g/802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20/40MHz
Wi-Fi Security	WPA-PSK/WPA2-PSK
Interface	
Communication Interface	1*RJ-45 (10/100 Base-T)
Built-in Mic	Yes
Built-in Speaker	Yes
Reset Button	Yes
On-board Storage	Support microSD/microSDHC/microSDXC card,up to 512GB

General	
Web Client Language	3 languages Simple Chinese/English/Vietnamese
Operating Temperature	-30℃~60℃(-22℉~140℉)
Operating Humidity	≤95%RH
Storage Temperature	-30℃~60℃(-22℉~140℉)
Storage Humidity	10%~95%RH(non-condensing)
Power Supply	DC12V±25%,Max. 13W
Protection	Surge4000V; ESD6000V; IP66
Boundary Dimensions	133(L)102(W)209(H)mm
Package Dimensions	160(L)160(W)215(H)mm
GrossWeight	0.83kg

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az