

Titan (KN-1811)

Keenetic Titan KN-1810 (AX3200) WiFi6 Dual Band Mesh 200+ qoşulma

Model	Titan (KN-1811)
Brend	Keenetic
WIFI	WiFi6
Genişlik	Dual band
Mesh	Mesh
Tezlik	2.4Ghz/5Ghz
Port sürəti	1000 mb/s
Qoşulma sayı	200+



Specification

Model number	KN-1811 (What's new?)
CPU	MT7622B 1350 MHz, dual core
RAM	512 MB DDR3
Flash memory, Dual Image	256 MB
Wi-Fi 2.4 + 5 GHz	☐
Wi-Fi class	AX3200
Antennas	5 dBi
Ethernet ports	5 x 1 Gbps, 1 x 2.5 Gbps
WPS/Wi-Fi button	☐
FN button	Yes, two buttons
USB ports	1 x USB 2.0, 1 x USB 3.0
3G/4G connection	Via a compatible USB modem
Telephony support	With Keenetic Linear (sold separately)
Mesh Wi-Fi System	☐
2.4 GHz Wi-Fi network	800 Mbps (802.11n)
5 GHz Wi-Fi network	2402 Mbps (802.11ax)
IPoE/PPPoE routing	Up to 2500 Mbps
L2TP/PPTP routing	Up to 1500 Mbps
Reading from a USB drive	Up to 270 MB/s (USB 3.0)
Seamless roaming 802.11k/r/v	☐
MU-MIMO	☐
Airtime Fairness	☐
Beamforming	☐
OFDMA	☐
Pre-configured Wi-Fi protection	☐
WEP, WPA-PSK	☐

WPA2-PSK, WPA2-Enterprise	☺
WPA3-PSK, WPA3-Enterprise, OWE	☺
Multi-SSID and Guest Network	☺
Access control by MAC address	☺
Wi-Fi Multimedia (WMM)	☺
IPoE, PPPoE, PPTP, L2TP, 802.1x	☺
Multi-WAN	☺
Policy routing	☺
Internet connection backup	☺
Ping Check connectivity monitor	☺
PPPoE/PPTP/L2TP pass-through	☺
VLAN IEEE 802.1Q	☺
Link aggregation	☺
Routing table (DHCP/Manual)	☺
IntelliQoS 2.0	☺
DHCP (client/server)	☺
IPv6 Dual Stack	☺
NAT	☺
IGMP	☺
UDP to HTTP proxy	☺
UPnP	☺
Manual port forwarding	☺
SPI firewall with protection against DoS attacks	☺
PPTP (client/server)	☺
L2TP over IPsec client/server	☺
OpenVPN client/server	☺
SSTP client/server	☺
Ethernet-over-IP, IP-IP, GRE	☺
IPsec VPN (client/server)	☺
WireGuard	☺
Dynamic DNS client	☺
Direct or cloud access via KeenDNS	☺
HTTPS security for access via KeenDNS	☺
SafeDNS parental control	☺
AdGuard ad blocker	☺
Traffic statistics per client	☺
Bandwidth limit per client	☺
Access schedule per client or interface	☺
Guest hotspot with authentication (Captive Portal)	☺
Mobile broadband modem support	☺
RAS, NDIS, CDC-Ethernet, QMI support	☺
File server and personal cloud	☺
FAT, FAT32, exFAT, NTFS, EXT2, EXT3, EXT4, HFS+ support	☺
CIFS/SMB	☺
AFP	☺
FTP, SFTP	☺
WebDAV	☺
Time Machine, File History support	☺
Support for third-party extension packages from the Entware and Debian repositories	☺
Download Station	☺
File server	☺

Media server	☒
Print server	☒
Cloud-based Remote Network Monitoring and Management	☒
Mobile app for Android and iOS	☒
Web Interface with the Initial Setup Wizard and HTTPS security	☒
Command Line (CLI) via TELNET/SSH	☒
An option to control from external network	☒
Backup and restore configuration	☒
Automatic OS updates	☒
System event logging	☒
Device dimensions excluding antenna, w x d x h	214 mm x 154 mm x 33 mm
Device weight	500 g
Operating temperature	0–40 °C
Operating humidity	20–95% non-condensing
Power supply voltage	100–240 V 50/60 Hz
Device	☒
Power adapter	12 V 2.5 A
Ethernet cable	☒
Quick start guide	☒