KEENETIC

Titan (KN-1811)

Kod: 00-00003805 · Routerlər



Keenetic Titan KN-1810 (AX3200) WiFi6 Dual Band Mesh 200+ qoşulma

Texniki göstəricilər

WiFi6 WIFI	**Dual band** Genişlik
Mesh Mesh	**2.4Ghz/5Ghz** Tezlik
1000 mb/s Port sürəti	**200+** Qoşulma sayı

Ətraflı məlumat

Model number	KN-1811
CPU	MT7622B 1350 MHz, dual core
RAM	512 MB DDR3
Flash memory, Dual Image	256 MB
Wi-Fi 2.4 + 5 GHz	✔
Wi-Fi class	AX3200
Antennas	5 dBi
Ethernet ports	5 x 1 Gbps, 1 x 2.5 Gbps
WPS/Wi-Fi button	✔
FN button	Yes, two buttons
USB ports	1 x USB 2.0, 1 x USB 3.0
3G/4G connection	Via a compatible USB modem
Telephony support	With Keenetic Linear (sold separately)
Mesh Wi-Fi System	✔
2.4 GHz Wi-Fi network	800 Mbps (802.11n)
5 GHz Wi-Fi network	2402 Mbps (802.11ax)
IPoE/PPPoE routing	Up to 2500 Mbps
L2TP/PPTP routing	Up to 1500 Mbps
Reading from a USB drive	Up to 270 MB/s (USB 3.0)
Seamless roaming 802.11k/r/v	✔
MU-MIMO	✔
Airtime Fairness	✔
Beamforming	✔
OFDMA	✔
Pre-configured Wi-Fi protection	✔

WEP, WPA-PSK	✔
WPA2-PSK, WPA2-Enterprise	✔
WPA3-PSK, WPA3-Enterprise, OWE	✔
Multi-SSID and Guest Network	✔
Access control by MAC address	✔
Wi-Fi Multimedia (WMM)	✔
IPoE, PPPoE, PPTP, L2TP, 802.1x	✔
Multi-WAN	✔
Policy routing	✔
Internet connection backup	✔
Ping Check connectivity monitor	✔
PPPoE/PPTP/L2TP pass-through	✔
VLAN IEEE 802.1Q	✔
Link aggregation	✔
Routing table (DHCP/Manual)	✔
IntelliQoS 2.0	✔
DHCP (client/server)	✔
IPv6 Dual Stack	✔
NAT	✔
IGMP	✔
UDP to HTTP proxy	✔
UPnP	✔
Manual port forwarding	✔
SPI firewall with protection against DoS attacks	✔
PPTP (client/server)	✔
L2TP over IPSec client/server	✔
OpenVPN client/server	✔
SSTP client/server	✔

Ethernet-over-IP, IP-IP, GRE	✔
IPsec VPN (client/server)	✔
WireGuard	✔
Dynamic DNS client	✔
Direct or cloud access via KeenDNS	✔
HTTPS security for access via KeenDNS	✔
SafeDNS parental control	✔
AdGuard ad blocker	✔
Traffic statistics per client	✔
Bandwidth limit per client	✔
Access schedule per client or interface	✔
Guest hotspot with authentication (Captive Portal)	✔
Mobile broadband modem support	✔
RAS, NDIS, CDC-Ethernet, QMI support	✔
File server and personal cloud	✔
FAT, FAT32, exFAT, NTFS, EXT2, EXT3, EXT4, HFS+ support	✔
CIFS/SMB	✔
AFP	✔
FTP, SFTP	✔
WebDAV	✔
Time Machine, File History support	✔
Support for third-party extension packages from the Entware and Debian repositories	✔
Download Station	✔
File server	✔
Media server	✔
Print server	✔
Cloud-based Remote Network Monitoring and Management	✔

Mobile app for Android and iOS	✔
Web Interface with the Initial Setup Wizard and HTTPS security	✔
Command Line (CLI) via TELNET/SSH	✔
An option to control from external network	✔
Backup and restore configuration	✔
Automatic OS updates	✔
System event logging	✔
Device dimensions excluding antenna, w x d x h	214 mm x 154 mm x 33 mm
Device weight	500 g
Operating temperature	0–40 °C
Operating humidity	20–95% non-condensing
Power supply voltage	100–240 V 50/60 Hz
Device	✔
Power adapter	12 V 2.5 A
Ethernet cable	✔
Quick start guide	✔

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az