TP-LINK

TL-ER5120

Kod: 00-00001719 · Routerlər



TP-Link TL-ER5120 — biznes və iri şəbəkələr üçün güclü Gigabit Load Balance routerdir. Çoxlu WAN dəstəyi, yük balanslaşdırma, VPN, firewall və peşəkar təhlükəsizlik funksiyaları ilə stabil və etibarlı internet bağlantısı təqdim edir. Kiçik və orta müəssisələr üçün mükəmməl seçimdir.

Texniki göstəricilər

Load Balance	**1000 mb/s**
Tip	Port sürəti

Ətraflı məlumat

SECURITY	
Access Control	Source/Destination IP Based Access Control
Filtering	MAC Filtering URL/Keywords Filtering
ARP Inspection	Sending GARP Packets ARP Scanning by WAN/LAN IP-MAC Binding
Attack Defense	TCP/UDP/ICMP Flood Defense Block TCP Scan (Stealth FIN/Xmas/Null) Block Ping from WAN

HARDWARE FEATURES	
Standards and Protocols	IEEE 802.3, IEEE802.3u, IEEE802.3ab TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DNS, PPTP, L2TP
Interface	1 Gigabit WAN port 3 Gigabit LAN/WAN ports 1 Gigabit LAN port
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Button	Reset Button
Power Supply	Internal Universal Power Supply AC100-240V~ 50/60Hz Input
Flash	32MB
DRAM	DDRIII 256MB
LED	PWR, SYS, Link/Act, Speed, WAN
Dimensions (W x D x H)	17.3x7.1x1.7 in.(440x180x44 mm)

PERFORMANCE	
Concurrent Session	150000
NAT(iMIX)	703Mbps
NAT(DHCP)	934Mbps
NAT(PPPoE)	868Mbps

BASIC FUNCTIONS	
WAN Connection Type	Static/Dynamic IP, PPPoE/Russian PPPoE, PPTP/Russian PPTP, L2TP/Russian L2TP, Bigpond Cable
MAC Clone	Modify WAN MAC Address
DHCP	DHCP Server/Client DHCP Address Reservation
IPv6	IPv6 Support
VLAN	802.1Q VLAN, Port VLAN
IPTV	Bridge, Custom

TRANSMISSION	
Load Balance	Intelligent Load Balance Link Backup (Timing, Failover) Online Detection
NAT	One-to-One NAT Multi-nets NAT Virtual Server Port Triggering FTP/H.323/SIP/IPsec/PPTP ALG UPnP
Routing	Static Routing Policy Routing
Session Limit	IP-based Session Limit
Bandwidth Control	IP-based Bandwidth Control

AUTHENTICATION	
Web Authentication	Local User Authentication, Radius Sever Authentication, Onekey Online

MANAGEMENT	
Service	Dynamic DNS (Dyndns, No-IP, Peanuthull, Comexe)
Maintenance	Web Management Interface Remote Management Export & Import Configuration SNMP Diagnostics(Ping & Traceroute) NTP Synchronize Syslog Support

OTHERS	
Certification	CE, FCC, RoHS
Package Contents	TL-ER5120 Power Cord Rack-mount Kit Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7/8/8.1/10 MAC OS, NetWare, UNIX or Linux
Environment	Operating Temperature: 0℃~40℃ (32℉~104℉) Storage Temperature: -40℃~70℃ (-40℉~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az