

# TL-LS1210GP

TP-LINK TL-LS1210GP (UN) 10-PORT GIGABIT DESKTOP SWITCH WITH 8-PORT POE+



Model	TL-LS1210GP
Brend	Tp-Link
PoE gücü	60 W
Port sayı	8 Port
PoE	PoE
Port sürati	1000mb/s

## Specification

HARDWARE FEATURES	
Interface	<ul style="list-style-type: none"> <li>• 9x 10/100/1000 Mbps RJ45 Ports (Ports 1-8 supports PoE+ output)</li> <li>• 1x Gigabit SFP Port</li> </ul>
Network Media	<ul style="list-style-type: none"> <li>• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m)</li> <li>• 100BASE-TX: UTP category 5, 5e cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m)</li> <li>• 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m)</li> </ul>
Fan Quantity	Fanless
Installation	<ul style="list-style-type: none"> <li>• Desktop</li> <li>• Wall Mounting</li> </ul>
Physical Security Lock	Yes
Power Supply	External Power Adapter(Output: 53.5VDC / 1.31A)
PoE+ Ports(RJ45)	<ul style="list-style-type: none"> <li>• Standard: 802.3at/802.3af compliant</li> <li>• PoE Ports: Ports 1-8, up to 30 W PoE output per port</li> <li>• PoE Power Budget: 61W</li> </ul>
Dimensions ( W x D x H )	8.2x4.9x1.0 in (209x126x26 mm)
Max Power Consumption	<ul style="list-style-type: none"> <li>• 7.3 W (220/50Hz. no PD connected)</li> <li>• 76.96 W (220/50Hz. with 61 W PD connected)</li> </ul>
Max Heat Dissipation	<ul style="list-style-type: none"> <li>• 24.82 BTU/h (no PD connected)</li> <li>• 261.66 BTU/h (with 61 W PD connected)</li> </ul>
PERFORMANCE	
Switching Capacity	20 Gbps
Packet Forwarding Rate	14.88 Mpps
MAC Address Table	4K
Jumbo Frame	16 KB

SOFTWARE FEATURES		HARDWARE FEATURES	
Advanced Features	<ul style="list-style-type: none"> <li>• Extend Mode Button (Ports 1–4, Up to 250 m PoE power supply and data transmission)</li> <li>• Isolation Mode Button (Ports 1–8)</li> <li>• PoE Auto Recovery Button (Ports 1–8)</li> <li>• Compatible With IEEE 802.3af/at Compliant PDs</li> <li>• IEEE802.3x Flow Control</li> <li>• 802.1p/DSCP QoS</li> <li>• IGMP Snooping</li> <li>• Green Technology</li> </ul>		
Transmission Method	Store-And-Forward		
OTHERS			
Certification	CE, FCC, RoHS		
Package Contents	<ul style="list-style-type: none"> <li>• LS1210GP</li> <li>• Power Adapter</li> <li>• Installation Guide</li> </ul>		
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing		