

TL-MR3420

TP-LINK TL-MR3420 3G/4G WIRELESS N ROUTER



Model	TL-MR3420
Brend	Tp-Link
WIFI	WiFi4
Port sürəti	100 mb/s
LTE	4G
Tezlik	2.4Ghz

Specification

HARDWARE FEATURES	
Interface	1 USB 2.0 Port for LTE/HSPA+/HSUPA/HSDPA/UMTS/EVDO USB Modem 1 10/100Mbps WAN Port, 4 10/100Mbps LAN Ports, support the auto-Negotiation and auto-MDI/MDIX
Button	WPS/Reset Button Wireless On/Off Switch Power On/Off Button
External Power Supply	9V/0.85A
Dimensions (W x D x H)	8*5.4*1.7 in. (204*138*44 mm)
Antenna Type	V1&V2 Omni directional, Detachable, Reverse SMA V3&V4 Omni directional, Undetachable, Reverse SMA
Antenna Gain	2x5dBi

WIRELESS FEATURES	
Wireless Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Frequency	2.4-2.4835GHz
Transmit Power	<20dBm
Wireless Security	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, Wireless MAC Filtering

SOFTWARE FEATURES	
Security	NAT Firewall, SPI Firewall, MAC / IP / Packet / Application / URL Filtering, Denial of Service(DoS), SYN Flooding, Ping of Death
Management	Web Based Configuration(HTTP), Web Based Firmware Upgrade

OTHERS	

Certification	CE, FCC, RoHS
Package Contents	3G/4G Wireless N Router TL-MR3420 2 Antennas Power supply unit Ethernet Cable Resource CD Quick Installation Guide
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ Windows 7, 8, 10, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°~40° (32°~104°) Storage Temperature: -40°~70° (-40°~158°) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing