

TL-MR6400

TP-LINK TL-MR6400 300 MBPS WIRELESS N 4G LTE ROUTER

Model	TL-MR6400
Brend	Tp-Link
WIFI	WiFi4
Port sürəti	100 mb/s
LTE	4G
Tezlik	2.4Ghz



Specification

HARDWARE FEATURES	
Ports	3× 10/100 Mbps LAN ports 1× 10/100 Mbps LAN/WAN Port 1× Nano SIM Card Slot 2× External SMA-F Antenna Interface
Button	WPS/RESET Button, WiFi ON/OFF Button
External Power Supply(EU)	9V/0.85A
Dimensions (W x D x H)	6.85 × 4.9 × 1.32 in. (174 × 124.5 × 33.5 mm)
Antenna Type	2× Detachable External 4G LTE Antennas

WIRELESS FEATURES	
Wireless Standards	IEEE 802.11b, 802.11g, 802.11n
Frequency	2.4 GHz
Signal Rate	300 Mbps at 2.4 GHz
Reception Sensitivity	11g 54M: -74 dBm 11n HT20: -71 dBm 11n HT40: -67 dBm
Transmit Power	<20 dBm (2.4 GHz)
Wireless Functions	Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics
WAN Failover	Yes
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

WIRELESS FEATURES	
Network Type	4G: FDD-LTE Cat4 (800/900/1800/2100/2600 MHz), TDD-LTE (2300/2500/2600 MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS (900/2100 MHz)

SOFTWARE FEATURES	
Quality of Service	WMM, QoS
Operating Modes	3G/4G Router, Wireless Router
Management	Access Control, Local Management, Remote Management
WAN Connection Type	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	TP-Link DDNS, DynDns, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec
Access Control	Parental Controls, Local Management Control, Host List, Access Control
Firewall Security	DoS, SPI Firewall, IP and MAC Address Binding
Protocols	Supports IPv4 and IPv6
Guest Network	2.4 GHz Guest Network
VPN Server	PPTP VPN, OpenVPN

OTHERS	
Certification	CE, RoHS
Package Contents	300Mbps Wireless N 4G LTE Router TL-MR6400 1.5m Power Adapter RJ45 Ethernet Cable Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browser or higher, or other Java-enabled browsers Nano SIM Card
Environment	Operating Temperature: 0~40 (32 ~104) Storage Temperature: -40~60 (-40 ~140) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing