

TL-SF1048

TP-LINK TL-SF1048 48-Port 10/100Mbps Rackmount Network Switch



Model	TL-SF1048
Brend	Tp-Link
Port sayı	48 Port
Port sürati	100mb/s

Specification

HARDWARE FEATURES	
Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
Interface	48 10/100Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Physical Security Lock	No
Power Supply	100-240VAC, 50/60Hz
Dimensions (W x D x H)	17.3*7.1*1.7 in. (440*180*44 mm)
Mounting	Rack Mountable
Max Power Consumption	9.9W(220V/50Hz)
Max Heat Dissipation	33.78BTU/h
PERFORMANCE	
Switching Capacity	9.6Gbps
Packet Forwarding Rate	7.14Mpps
MAC Address Table	8K
Advanced Functions	Green Technology 802.3X Flow Control
Transfer Method	Store-and-Forward
OTHERS	
Certification	FCC, CE, RoHS

HARDWARE FEATURES

Package Contents	48-Port 10/100Mbps Rackmount Switch Power Cord Installation Guide Rackmount Kit Rubber Feet
System Requirements	Microsoft® Windows® XP, Vista™, Windows 7 or Windows 8, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°~40° (32°~104°); Storage Temperature: -40°~70° (-40°~158°); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing